

PIQUE ADVANCED 29 3



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Ice Age/Carbon
FRAME	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension
FORK	RockShox Sid, 120mm, Boost 15x110mm Maxle Stealth, tapered, tapered, 44mm offset, Rush RL
SHOCK	Fox Float SL Performance, 165x45, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact XC, alloy, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm
GRIPS	Liv XC Pro, 32mm silicone
STEM	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
SEATPOST	Giant Contact Switch, adjustable dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
SADDLE	Fi'zi:k Vento Argo R5
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Deore M6100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore M6100, Shadow +
BRAKES	Shimano BR MT4100, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano MT-401
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	KMC X12
CRANKSET	Praxis Cadet, steel chainring 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 175mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant XCR 2 29 carbon WheelSystem, 25mm inner width
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks.

Suggested Retail Price (CDN): \$5,499.00

FRAME GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	380	410	440	470
Seat Post Insertion Depth (mm)	203	233	263	293
Seat Tube Angle	76.0°	76.0°	76.0°	76.0°
Top Tube Length (mm)	555	570	585	600
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67.0°	67.0°	67.0°	67.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	112.2	112.2	112.2	112.2
Wheelbase (mm)	1121	1137	1154	1170
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	45	45	45	45
Stack (mm)	599	603	612	622
Reach (mm)	406	420	432	445
Stand Over Height (mm)	748	767	770	791
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	175
Wheel Size	29"	29"	29"	29"

All prices and specifications are subject to change without notice.