

PIQUE ADVANCED 29 3



SPECS

| RAMME | |
|----------------|--|
| STØRRELSE | XS, S, M, L |
| FARGE | Ice Age/Carbon |
| RAMME | Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension, 12x148mm thru-axle |
| GAFFEL | RockShox Sid, 120mm, Boost 15x110mm Maxle Stealth, tapered, 44mm offset, Rush RL damper |
| DEMPER | Fox Float SL Performance, 165x45, custom tuned for Liv, recommended sag 25% |
| KOMPONENTER | |
| STYRE | Giant Contact XC Flat, alloy, 760x35mm |
| GRIPS | Liv XC Pro, 32mm |
| STYRSTEM | Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm |
| SETEPINNE | Giant Contact Switch Core dropper, remote XS: 100mm travel / 30.9 x 350mm S: 100mm travel / 30.9 x 350mm M: 100mm travel / 30.9 x 350mm L: 120mm travel / 30.9 x 400mm |
| SADEL | Liv Grit |
| DRIVVERK | |
| GIRHENDLER | Shimano Deore SL-M6100, 1x12 |
| FRONTGIR | N/A |
| BAKGIR | Shimano SLX RD-M7100 |
| BREMSER | Shimano Deore MT410, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm |
| BREMSEHENDLER | Shimano Deore MT401 |
| KASSETT | Shimano SLX, M7100, 10x51 |
| KJEDE | KMC X-12 |
| KRANK | Praxis Cadet, 30t, 55mm chainline XS:165mm, S:170mm, M:170mm, L:175mm |
| BOTTOM BRACKET | Praxis, press fit |

| HJUL | |
|--------|--|
| FELG | Giant XCT 29, 25mm inner width |
| NAV | Shimano C500, sealed |
| EIKE | stainless steel |
| DEKK | Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless |
| EXTRAS | tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t |

GEOMETRI

| RAMME | XS | S | M | L |
|--------------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 380 | 410 | 440 | 470 |
| Seat Post Insertion Depth (mm) | 203 | 233 | 263 | 293 |
| Seat Tube Angle | 76,0° | 76,0° | 76,0° | 76,0° |
| Top Tube Length (mm) | 555 | 570 | 585 | 600 |
| Head Tube Length (mm) | 90 | 95 | 105 | 115 |
| Head Tube Angle | 67,0° | 67,0° | 67,0° | 67,0° |
| Fork Rake (mm) | 44 | 44 | 44 | 44 |
| Trail (mm) | 112,2 | 112,2 | 112,2 | 112,2 |
| Wheelbase (mm) | 1121 | 1137 | 1154 | 1170 |
| Chain Stay Length (mm) | 435 | 435 | 435 | 435 |
| Bottom Bracket Drop (mm) | 45 | 45 | 45 | 45 |
| Stack (mm) | 599 | 603 | 612 | 622 |
| Reach (mm) | 406 | 420 | 432 | 445 |
| Stand Over Height (mm) | 748 | 767 | 770 | 791 |
| Handlebar Width (mm) | 760 | 760 | 760 | 760 |
| Stem Length (mm) | 60 | 60 | 70 | 70 |
| Crank Length (mm) | 165 | 170 | 170 | 175 |
| Wheel Size | 29" | 29" | 29" | 29" |

Alle spesifikasjonene kan endres uten varsel.