

PIQUE ADVANCED 29 3



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Ice Age/Carbon
OKVIR	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension, 12x148mm thru-axle
VILICE	RockShox Sid, 120mm, Boost 15x110mm Maxle Stealth, tapered, 44mm offset, Rush RL damper
AMORTIZER	Fox Float SL Performance, 165x45, custom tuned for Liv, recommended sag 25%
KOMPONENTE	
KRMILO	Giant Contact XC Flat, alloy, 760x35mm
GRIPS	Liv XC Pro, 32mm
OPORA KRMILA	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
OPORA SEDEŽA	Giant Contact Switch Core dropper, remote XS: 100mm travel / 30.9 x 350mm S: 100mm travel / 30.9 x 350mm M: 100mm travel / 30.9 x 350mm L: 120mm travel / 30.9 x 400mm
SEDEŽ	Liv Grit
POGON	
PRESTAVNE ROČICE	Shimano Deore SL-M6100, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano SLX RD-M7100
ZAVORE	Shimano Deore MT410, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Shimano Deore MT401
VERIŽNIK	Shimano SLX, M7100, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Praxis Cadet, 30t, 55mm chainline XS:165mm, S:170mm, M:170mm, L:175mm
BOTTOM BRACKET	Praxis, press fit

OBROČNIKI	
OBROČI	Giant XCT 29, 25mm inner width
PESTA	Shimano C500, sealed
NAPERE	stainless steel
PLAŠČI	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
DODATKI	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	380	410	440	470
Seat Post Insertion Depth (mm)	203	233	263	293
Kot sedežne cevi	76,0°	76,0°	76,0°	76,0°
Top Tube Length (mm)	555	570	585	600
Višina glave okvirja (mm)	90	95	105	115
Krmilni kot	67,0°	67,0°	67,0°	67,0°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	112,2	112,2	112,2	112,2
Medosna razdalja (mm)	1121	1137	1154	1170
Dolžina cevi ob verigi (mm)	435	435	435	435
Bottom Bracket Drop (mm)	45	45	45	45
Oddaljenost zgornje cevi od gonilne osi (mm)	599	603	612	622
Doseg (mm)	406	420	432	445
Višina zgornje cevi (mm)	748	767	770	791
Širina krmila (mm)	760	760	760	760
Dolžina opore krmila (mm)	60	60	70	70
Dolžina gonilke (mm)	165	170	170	175
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.