

PIQUE ADVANCED SL 1



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, L
ЦВЯТ	Lake Green/Black
РАМКА	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
ВИЛКА	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
ЗАДЕН АМОРТИСЬОР	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
КОМПОНЕНТИ	
КОРМИЛО	Giant Integrated XC, composite, 780mm, 9-degree upsweep
ГРИПОВЕ	SRAM TwistLoc Ultimate
ЛАПА	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
СЕДАЛКА	Liv Grit SL
ПЕДАЛИ	N/A
DRIVETRAIN	
КОМАНДИ	SRAM AXS Pod, discrete clamp, 1x12
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	SRAM GX AXS Transmission
СПИРАЧКИ	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano Deore XT BL-M8100
КАСЕТА	SRAM XS 1275, 10x52
ВЕРИГА	SRAM GX Transmission
КУРБЕЛ	SRAM GX Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШНИ	Giant XCR Carbon WheelSystem
ГЛАВИНИ	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
СПИЦИ	Sapim
ГУМИ	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
ЕКСТРИ	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

ГЕОМЕТРИЯ

РАМКА	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		410		440		470	
Seat Tube Angle	75,5° 76,0°		75,5° 76,0°		75,5° 76,0°		75,5° 76,0°	
Top Tube Length (mm)	555	554	572	571	594	593	611	610
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66,5° 67,0°		66,5° 67,0°		66,5° 67,0°		66,5° 67,0°	
Fork Rake (mm)	44		44		44		44	
Trail (mm)	116	112	116	112	116	112	116	112
Wheelbase (mm)	1121	1120	1138	1138	1162	1162	1181	1180
Chain Stay Length (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	51	45	51	45	51	45	51	45
Stack (mm)	602	599	607	603	616	612	625	622
Обсер (mm)	399	405	415	421	435	440	450	455
Stand Over Height (mm)	772	778	770	776	765	765	759	765
Ширина на Кормило (mm)	780		780		780		780	
Дължина на Лапа (mm)	60		60		70		70	
Дължина на Курбел (mm)	165		170		170		170	

All specifications listed are subject to change without notice.