PIQUE ADVANCED SL 1



SPEZIFIKATIONEN

RAHMEN & GABEL	
RAHMENGRÖSSEN	XS, S, M, L
FARBE(N)	Lake Green/Black
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GABEL	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
DÄMPFER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COCKPIT	
LENKER	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIFFE	SRAM TwistLoc Ultimate
VORBAU	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
SATTELSTÜTZE	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
SATTEL	Liv Grit SL
PEDALE	N/A
SCHALTUNG, ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod, discrete clamp, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX AXS Transmission
BREMSEN	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BREMSHEBEL	Shimano Deore XT BL-M8100
KASSETTE	SRAM XS 1275, 10x52
KETTE	SRAM GX Transmission
KURBELSATZ	SRAM GX Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
INNENLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant XCR Carbon WheelSystem
NABEN (V/H)	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPEICHEN	Sapim
REIFEN	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
ZUBEHÖR (TEILW. VERBAUT)	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

UVP: 7.000,00 €

GEOMETRIEDATEN

RAHMEN & GABEL	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Sitzrohrlänge (mm)	400	410	440	470
Sitzwinkel	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Oberrohrlänge (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Steuerrohrlänge (mm)	90	95	105	115
Lenkwinkel	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Gabelvorbiegung (mm)	44	44	44	44
Gabelnachlauf (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Radstand (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Kettenstrebenlänge (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Tretlagerabsenkung (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Reach (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Überstands-/Durchstiegshöhe (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	60	60	70	70
Kurbelarmlänge (mm)	165	170	170	170

Spezifikations-, Preis- und Farbänderungen vorbehalten.