

PIQUE ADVANCED SL 1



SPECS

FRAME	
SIZES	XS, S, M
COLORS	Lake Green/Black
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
SHOCK	RockShox SidLux Select+, RL damper, Solo Air, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
STEM	Giant Integrated XC Carbon XS:60mm, S:60mm, M:70mm
SEATPOST	Giant Contact Switch SL dropper XS: 110mm travel / 30.9 x 340mm S: 110mm travel / 30.9 x 340mm M: 140mm travel / 30.9 x 390mm
SADDLE	Liv Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle T-Type AXS
BRAKES	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XS-1275, T-Type 10x52
CHAIN	SRAM GX T-Type
CRANKSET	SRAM GX Transmission, 34t, 55mm chainline XS:165mm, S:170mm, M:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCR Carbon WheelSystem
HUBS	[F] Giant alloy, 6-bolt [R] Giant Alloy, 120T Helical-Bevel Ratchet Driver, 6-Bolt
SPOKES	Carbon
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	Tubeless prepared, 2.4" max tyre size, 34t max chainring size, MRP 1x SL TR2 chain guide

Price: \$12,999.00

GEOMETRY

FRAME	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	410	440	470
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Top Tube Length (mm)	555 554	572 571	594 593	611 610
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 112	116 112	116 112	116 112
Wheelbase (mm)	1121 1120	1138 1138	1162 1162	1181 1180
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	51 45	51 45
Stack (mm)	602 599	607 603	616 612	625 622
Reach (mm)	399 405	415 421	435 440	450 455
Stand Over Height (mm)	772 778	770 776	765 765	759 765
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	170

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.