PIQUE ADVANCED SL 1



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Lake Green/Black
CUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
HORQUILLA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTIGUADOR	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTES	
MANILLAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
PUÑOS	SRAM TwistLoc Ultimate
POTENCIA	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
TIJA DE SILLÍN	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
SILLÍN	Liv Grit SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Pod, discrete clamp, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX AXS Transmission
FRENOS	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano Deore XT BL-M8100
CASETTE	SRAM XS 1275, 10x52
CADENA	SRAM GX Transmission
JGO. PLATOS Y BIELAS	SRAM GX Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant XCR Carbon WheelSystem
BUJES	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RADIOS	Sapim
CUBIERTAS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Precio: 6.499,00 €

GEOMETRÍA

CUADRO	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Longitud del tubo del sillín (mm)	400	410	440	470
Ángulo del tubo del sillín	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Longitud del tubo superior (mm) (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Longitud del tubo de dirección (mm) (mm)	90	95	105	115
Ángulo del tubo de dirección	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Inclinación de la horquilla (mm)	44	44	44	44
Trail (mm) (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Distancia entre ejes (mm) (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Longitud de la vaina (mm) (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Caída del eje de pedalier (mm) (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Stack (mm) (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Reach (mm) (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Altura del suelo al tubo (mm) (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Ancho del manillar (mm) (mm)	780	780	780	780
Longitud de la potencia (mm) (mm)	60	60	70	70
Longitud de las bielas (mm) (mm)	165	170	170	170

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.