

PIQUE ADVANCED SL 1



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Lake Green/Black
CUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
TIJERA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTIGUADOR	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTES	
MANUBRIO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
POTENCIA	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
POSTE DE ASIENTO	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
ASIENTO	Liv Grit SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Pod, discrete clamp, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX AXS Transmission
FRENOS	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XS 1275, 10x52
CADENA	SRAM GX Transmission
MULTIPLICACIÓN	SRAM GX Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant XCR Carbon WheelSystem
MAZAS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAYOS	Sapim
NEUMÁTICOS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Precio: \$149,990.00

GEOMETRÍA

CUADRO	XS		S		M	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	400	410	410	420	440	450
Ángulo de la Base del Poste de Asiento	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Longitud del Tubo Superior (mm)	555 554	572 571	594 593	594 593	594 593	594 593
Longitud del Telescopio (mm)	90	95	105	105	105	105
Ángulo del Telescopio	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Rake (mm)	44	44	44	44	44	44
Trail (mm)	116 112	116 112	116 112	116 112	116 112	116 112
Distancia entre Ejes (mm)	1121 1120	1138 1138	1162 1162	1162 1162	1162 1162	1162 1162
Longitud de Vaina Inferior (mm)	437 435	437 435	437 435	437 435	437 435	437 435
Caída del Eje de Centro (mm)	51 45	51 45	51 45	51 45	51 45	51 45
Stack (mm)	602 599	607 603	616 612	616 612	616 612	616 612
Reach (mm)	399 405	415 421	435 440	435 440	435 440	435 440
Altura del Tubo Superior al Suelo (mm)	772 778	770 776	765 765	765 765	765 765	765 765
Ancho del Manubrio (mm)	780	780	780	780	780	780
Longitud de la Potencia (mm)	60	60	70	70	70	70
Longitud de la Biela (mm)	165	170	170	170	170	170

Todas las especificaciones están sujetas a cambios sin previo aviso.