

# PIQUE ADVANCED SL 1



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLORS</b>	Lake Green/Black
<b>FRAME</b>	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
<b>FORK</b>	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
<b>SHOCK</b>	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
<b>HANDLEBAR</b>	Giant Integrated XC, composite, 780mm, 9-degree upsweep
<b>GRIPS</b>	SRAM TwistLoc Ultimate
<b>STEM</b>	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
<b>SEATPOST</b>	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
<b>SADDLE</b>	Liv Grit SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM AXS Pod, discrete clamp, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM GX AXS Transmission
<b>BRAKES</b>	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano Deore XT BL-M8100
<b>CASSETTE</b>	SRAM XS 1275, 10x52
<b>CHAIN</b>	SRAM GX Transmission
<b>CRANKSET</b>	SRAM GX Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant XCR Carbon WheelSystem
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
<b>SPOKES</b>	Sapim
<b>TIRES</b>	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
<b>EXTRAS</b>	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

## GEOMETRY

FRAME	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	410	440	470				
Seat Tube Angle	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°	75,5°   76,0°				
Top Tube Length (mm)	555   554	572   571	594   593	611   610				
Head Tube Length (mm)	90	95	105	115				
Head Tube Angle	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°	66,5°   67,0°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	116   112	116   112	116   112	116   112				
Wheelbase (mm)	1121   1120	1138   1138	1162   1162	1181   1180				
Chain Stay Length (mm)	437   435	437   435	437   435	437   435				
Bottom Bracket Drop (mm)	51   45	51   45	51   45	51   45				
Stack (mm)	602   599	607   603	616   612	625   622				
Reach (mm)	399   405	415   421	435   440	450   455				
Stand Over Height (mm)	772   778	770   776	765   765	759   765				
Handlebar Width (mm)	780	780	780	780				
Stem Length (mm)	60	60	70	70				
Crank Length (mm)	165	170	170	170				

All specifications listed are subject to change without notice.