

PIQUE ADVANCED SL 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Lake Green/Black
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
SHOCK	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
STEM	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
SEATPOST	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
SADDLE	Liv Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX AXS Transmission
BRAKES	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XS 1275, 10x52
CHAIN	SRAM GX Transmission
CRANKSET	SRAM GX Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCR Carbon WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Suggested Retail Price (CDN): \$8,699.00

FRAME GEOMETRY

FRAME	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		410		440		470	
Seat Tube Angle	75.5° 76.0°		75.5° 76.0°		75.5° 76.0°		75.5° 76.0°	
Top Tube Length (mm)	555	554	572	571	594	593	611	610
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66.5° 67.0°		66.5° 67.0°		66.5° 67.0°		66.5° 67.0°	
Fork Rake (mm)	44		44		44		44	
Trail (mm)	116	112	116	112	116	112	116	112
Wheelbase (mm)	1121	1120	1138	1138	1162	1162	1181	1180
Chain Stay Length (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	51	45	51	45	51	45	51	45
Stack (mm)	602	599	607	603	616	612	625	622
Reach (mm)	399	405	415	421	435	440	450	455
Stand Over Height (mm)	772	778	770	776	765	765	759	765
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	60		60		70		70	
Crank Length (mm)	165		170		170		170	

All prices and specifications are subject to change without notice.