

PIQUE ADVANCED SL 1



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Lake Green/Black
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTIZER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTE	
VOLAN	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
LULA VOLANA	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
CIJEV SJEDALA	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
SJEDALO	Liv Grit SL
PEDALE	N/A
POGON	
RUČICE MJENJAČA	SRAM AXS Pod, discrete clamp, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM GX AXS Transmission
KOČNICE	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
RUČICE KOČNICA	Shimano Deore XT BL-M8100
KAZETA	SRAM XS 1275, 10x52
LANAC	SRAM GX Transmission
POGON	SRAM GX Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant XCR Carbon WheelSystem
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
ŽBICE	Sapim
GUME	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DODACI	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

GEOMETRIJA

OKVIR	XS		S		M		L
	LOW	HIGH	LOW	HIGH	LOW	HIGH	
Dužina cijevi sjedala (mm)	400	410	440				4
Kut cijevi sjedala	75,5°	76,0°	75,5°	76,0°	75,5°	76,0°	7
Dužina gornje cijevi (mm)	555	554	572	571	594	593	6
Dužina prednje cijevi (mm)	90		95		105		1
Kut vilice	66,5°	67,0°	66,5°	67,0°	66,5°	67,0°	6
Zakrivljenost vilice (offset) (mm)	44		44		44		4
Staza (mm)	116	112	116	112	116	112	1
Međuosovinski razmak kotača (mm)	1121	1120	1138	1138	1162	1162	1
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	437	435	437	435	437	435	4
Položaj osovine pogona (mm)	51	45	51	45	51	45	5
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	602	599	607	603	616	612	6
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	399	405	415	421	435	440	4
Prekoračna visina (mm)	772	778	770	776	765	765	7
Širina volana (mm)	780		780		780		7
Dužina lule volana (mm)	60		60		70		7
Dužina poluge pedale (mm)	165		170		170		1

Sve navedene specifikacije podložne su promjeni bez prethodne najave.