

PIQUE ADVANCED SL 1



SPECS

QUADRO	
TAMANHOS	XS, S, M, L
CORES	Lake Green/Black
QUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORQUILHA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTECEDORES	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTES	
GUIADOR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
PUNHOS	SRAM TwistLoc Ultimate
AVANÇO	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
ESPIGÃO DE SELIM	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
SELIM	Liv Grit SL
PEDAIS	N/A
TRANSMISSÃO	
MANETES	SRAM AXS Pod, discrete clamp, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	SRAM GX AXS Transmission
TRAVÕES	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Shimano Deore XT BL-M8100
CASSETTE	SRAM XS 1275, 10x52
CORRENTE	SRAM GX Transmission
CONJUNTO PEDALEIRO	SRAM GX Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant XCR Carbon WheelSystem
CUBOS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAIOS	Sapim
PNEUS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Preço: 5 699,00 €

GEOMETRIA

QUADRO	XS	S	M
	LOW HIGH	LOW HIGH	LOW HIGH
Comprimento do tubo do assento (mm)	400	410	440
Ângulo do tubo do assento	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Comprimento do tubo superior (mm)	555 554	572 571	594 593
Comprimento do tubo principal (mm)	90	95	105
Ângulo do tubo principal	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Garfo ancinho (mm)	44	44	44
Trilha (mm)	116 112	116 112	116 112
distância entre eixos (mm)	1121 1120	1138 1138	1162 1162
Comprimento Chain Stay (mm)	437 435	437 435	437 435
Suporte inferior (mm)	51 45	51 45	51 45
Pilha (mm)	602 599	607 603	616 612
Alcançar (mm)	399 405	415 421	435 440
Altura do standover (mm)	772 778	770 776	765 765
Largura do guidão (mm)	780	780	780
Comprimento da haste (mm)	60	60	70
Comprimento da Manivela (mm)	165	170	170

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.