

PIQUE ADVANCED SL 1



ŠPECIFIKÁCIE

| RÁM | |
|-------------------|---|
| VELKOSTI | XS, S, M, L |
| FARBY | Lake Green/Black |
| RÁM | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle |
| VIDLICA | RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout |
| TLMÍČ | RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate |
| KOMPONENTY | |
| RIADIDLÁ | Giant Integrated XC, composite, 780mm, 9-degree upsweep |
| GRIPY | SRAM TwistLoc Ultimate |
| PREDSTAVEC | Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm |
| SEDLOVKA | Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel |
| SEDADLO | Liv Grit SL |
| PEDÁLE | N/A |
| POHON | |
| RADENIE | SRAM AXS Pod, discrete clamp, 1x12 |
| PREŠMYKAČ | N/A |
| PREHADZOVAČKA | SRAM GX AXS Transmission |
| BRZDY | Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm |
| BRZDOVÉ PÁKY | Shimano Deore XT BL-M8100 |
| KAZETA | SRAM XS 1275, 10x52 |
| REŤAZ | SRAM GX Transmission |
| KLUKY | SRAM GX Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm |
| STREDOVÉ ZLOŽENIE | SRAM DUB, press fit |

| KOLESÁ | |
|------------|---|
| RÁFIKY | Giant XCR Carbon WheelSystem |
| NÁBOJE | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt |
| ŠPICE | Sapim |
| PNEUMATIKY | Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless |
| DOPLNKY | tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide |

Cena: 7 299 €

GEOMETRIA

| RÁM | XS | S | M | L |
|--|---------------|---------------|---------------|---------------|
| Dĺžka sedlovej trubky (mm) | LOW HIGH | LOW HIGH | LOW HIGH | LOW HIGH |
| Uhol sedlovej trubky | 75,5° 76,0° | 75,5° 76,0° | 75,5° 76,0° | 75,5° 76,0° |
| Dĺžka hornej rámovej trubky (mm) | 555 554 | 572 571 | 594 593 | 611 610 |
| Dĺžka hlavovej trubky (mm) | 90 | 95 | 105 | 115 |
| Uhol hlavovej trubky | 66,5° 67,0° | 66,5° 67,0° | 66,5° 67,0° | 66,5° 67,0° |
| Offset vidlice (mm) | 44 | 44 | 44 | 44 |
| Trail (mm) | 116 112 | 116 112 | 116 112 | 116 112 |
| Rázvor (mm) | 1121 1120 | 1138 1138 | 1162 1162 | 1181 1180 |
| Dĺžka zadnej stavby (mm) | 437 435 | 437 435 | 437 435 | 437 435 |
| Rozdiel zadnej voči stredovej osi - BB DROP (mm) | 51 45 | 51 45 | 51 45 | 51 45 |
| Stack - výška riadenia (mm) | 602 599 | 607 603 | 616 612 | 625 622 |
| Reach (mm) | 399 405 | 415 421 | 435 440 | 450 455 |
| Výška rámu od zeme (mm) | 772 778 | 770 776 | 765 765 | 759 765 |
| Šírka riaditok (mm) | 780 | 780 | 780 | 780 |
| Dĺžka predstavca (mm) | 60 | 60 | 70 | 70 |
| Dĺžka klúku (mm) | 165 | 170 | 170 | 170 |

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.