PIQUE ADVANCED SL 2



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Dreamy Blue/Black
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORGAFFEL	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
BAGDÆMPER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTER	
STYR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GREB / STYRBÅND	SRAM TwistLoc Ultimate
FREMPIND	Giant Integrated XC, alloy XS: 60, S:60mm, M:70mm, L:70mm
SADELPIND	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
SADEL	Liv Grit SL
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	SRAM Eagle 90 mechanical, 1x12
FORSKIFTER	N/A
BAGSKIFTER	SRAM Eagle 90 Transmission
BREMSER	Shimano SLX BR-M7100, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
BREMSEGREB	Shimano SLX BL-M7100
KASSETTE	SRAM 70 1270, 10x52
KÆDE	SRAM 70 Transmission
KRANKSÆT	SRAM 90 Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant XCA WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
EGER	Sapim
DÆK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EKSTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Pris: 43.669,00 kr.

GEOMETRI

RAMME	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Sadelrørslængde (mm)	400	410	440	470
Sadelrørsvinkel	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Overrørslængde (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Kronrørslængde (mm)	90	95	105	115
Kronrøsvinkel	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Forgaffel fremspring (rake) (mm)	44	44	44	44
Sti (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Akselafstand (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Kædestagslængde (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Krankboks drop (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Reach (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Skridthøjde (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Styrbredde (mm)	780	780	780	780
Frempindslængde (mm)	60	60	70	70
Pedalarmslængde (mm)	165	170	170	170

Alle de anførte specifikationer kan ændres uden varsel.