



# PIQUE ADVANCED SL 2



## SPECS

| FRAME            |                                                                                                                     |
|------------------|---------------------------------------------------------------------------------------------------------------------|
| SIZES            | XS, S, M, L                                                                                                         |
| COLOURS          | Dreamy Blue/Black                                                                                                   |
| FRAME            | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle |
| FORK             | RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout                |
| SHOCK            | RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate                                            |
| COMPONENTS       |                                                                                                                     |
| HANDLEBAR        | Giant Integrated XC, alloy, 780mm, 9-degree upsweep                                                                 |
| GRIPS            | SRAM TwistLoc Ultimate                                                                                              |
| STEM             | Giant Integrated XC, alloy XS: 60, S:60mm, M:70mm, L:70mm                                                           |
| SEATPOST         | Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel                            |
| SADDLE           | Liv Grit SL                                                                                                         |
| PEDALS           | N/A                                                                                                                 |
| DRIVETRAIN       |                                                                                                                     |
| SHIFTERS         | SRAM Eagle 90 mechanical, 1x12                                                                                      |
| FRONT DERAILLEUR | N/A                                                                                                                 |
| REAR DERAILLEUR  | SRAM Eagle 90 Transmission                                                                                          |
| BRAKES           | Shimano SLX BR-M7100, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm                                               |
| BRAKE LEVERS     | Shimano SLX BL-M7100                                                                                                |
| CASSETTE         | SRAM 70 1270, 10x52                                                                                                 |
| CHAIN            | SRAM 70 Transmission                                                                                                |
| CRANKSET         | SRAM 90 Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm                                      |
| BOTTOM BRACKET   | SRAM DUB, press fit                                                                                                 |

| WHEELS |                                                                                       |
|--------|---------------------------------------------------------------------------------------|
| RIMS   | Giant XCA WheelSystem                                                                 |
| HUBS   | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt               |
| SPOKES | Sapim                                                                                 |
| TIRES  | Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless                       |
| EXTRAS | tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide |

Suggested Retail Price (CDN): \$7,499.00

## FRAME GEOMETRY

| FRAME                    | XS            | S             | M             | L             |
|--------------------------|---------------|---------------|---------------|---------------|
|                          | LOW   HIGH    | LOW   HIGH    | LOW   HIGH    | LOW   HIGH    |
| Seat Tube Length (mm)    | 400           | 410           | 440           | 470           |
| Seat Tube Angle          | 75.5°   76.0° | 75.5°   76.0° | 75.5°   76.0° | 75.5°   76.0° |
| Top Tube Length (mm)     | 555   554     | 572   571     | 594   593     | 611   610     |
| Head Tube Length (mm)    | 90            | 95            | 105           | 115           |
| Head Tube Angle          | 66.5°   67.0° | 66.5°   67.0° | 66.5°   67.0° | 66.5°   67.0° |
| Fork Rake (mm)           | 44            | 44            | 44            | 44            |
| Trail (mm)               | 116   112     | 116   112     | 116   112     | 116   112     |
| Wheelbase (mm)           | 1121   1120   | 1138   1138   | 1162   1162   | 1181   1180   |
| Chain Stay Length (mm)   | 437   435     | 437   435     | 437   435     | 437   435     |
| Bottom Bracket Drop (mm) | 51   45       | 51   45       | 51   45       | 51   45       |
| Stack (mm)               | 602   599     | 607   603     | 616   612     | 625   622     |
| Reach (mm)               | 399   405     | 415   421     | 435   440     | 450   455     |
| Stand Over Height (mm)   | 772   778     | 770   776     | 765   765     | 759   765     |
| Handlebar Width (mm)     | 780           | 780           | 780           | 780           |
| Stem Length (mm)         | 60            | 60            | 70            | 70            |
| Crank Length (mm)        | 165           | 170           | 170           | 170           |

All prices and specifications are subject to change without notice.