PIQUE ADVANCED SL 2



SPECS

CADRU	
MARIMI	XS, S, M, L
CULORI	Dreamy Blue/Black
CADRU	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FURCA	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
SOC	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTE	
GHIDON	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
PIPA	Giant Integrated XC, alloy XS: 60, S:60mm, M:70mm, L:70mm
TIJA SA	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
SA	Liv Grit SL
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM Eagle 90 mechanical, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	SRAM Eagle 90 Transmission
FRANE	Shimano SLX BR-M7100, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
MANETE FRANA	Shimano SLX BL-M7100
PINIOANE	SRAM 70 1270, 10x52
LANT	SRAM 70 Transmission
ANGRENAJ	SRAM 90 Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant XCA WheelSystem
BUTUCI	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPITE	Sapim
ANVELOPE	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

GEOMETRIE

CADRU	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	400	410	440	470
Seat Tube Angle	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Top Tube Length (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Wheelbase (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Chain Stay Length (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Reach (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Stand Over Height (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	170

Toate specificatiile enumerate se pot schimba fara notificare prealabila.