PIQUE ADVANCED SL 2



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Dreamy Blue/Black
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
VILICE	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
AMORTIZER	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTE	
KRMILO	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
OPORA KRMILA	Giant Integrated XC, alloy XS: 60, S:60mm, M:70mm, L:70mm
OPORA SEDEŽA	Giant Contact Switch SL dropper, remote XS: 110mm travel S: 110mm travel M: 140mm travel
SEDEŽ	Liv Grit SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM Eagle 90 mechanical, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM Eagle 90 Transmission
ZAVORE	Shimano SLX BR-M7100, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Shimano SLX BL-M7100
VERIŽNIK	SRAM 70 1270, 10x52
VERIGA	SRAM 70 Transmission
GONILKE Z VERIŽNIKI	SRAM 90 Transmission, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant XCA WheelSystem
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
NAPERE	Sapim
PLAŠČI	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
DODATKI	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

GEOMETRIJA

OKVIR	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Dolžina sedežne cevi (mm)	400	410	440	470
Kot sedežne cevi	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Top Tube Length (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Višina glave okvirja (mm)	90	95	105	115
Krmilni kot	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Medosna razdalja (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Dolžina cevi ob verigi (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Oddaljenost zgornje cevi od gonilne osi (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Doseg (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Višina zgornje cevi (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Širina krmila (mm)	780	780	780	780
Dolžina opore krmila (mm)	60	60	70	70
Dolžina gonilke (mm)	165	170	170	170

Vse navedene specifikacije se lahko spremenijo brez obvestila.