

PIQUE ADVANCED SL 3



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Deep Cove/Sea Sparkle
CUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
HORQUILLA	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
AMORTIGUADOR	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout
COMPONENTES	
MANILLAR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
PUÑOS	Liv XC Pro, silicone
POTENCIA	Giant Integrated XC, alloy XS: 60, S:60mm, M:70mm, L:70mm
TIJA DE SILLÍN	Giant Core dropper, remote XS: 100mm travel / 30.9 x 395mm S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm
SILLÍN	Liv Grit
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore mechanical, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano Deore
FRENOS	Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano BL-MT501
CASETTE	Shimano M6100, 10x51
CADENA	KMC X-12
JGO. PLATOS Y BIELAS	Praxis Cadet HD M24, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
CAJA DE PEDALIER	Praxis, press fit

RUEDAS	
LLANTAS	Giant XCA WheelSystem
BUJES	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RADIOS	Sapim
CUBIERTAS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Precio: 4.299,00 €

GEOMETRÍA

CUADRO	XS	S	M
	LOW HIGH	LOW HIGH	LOW HIGH
Longitud del tubo del sillín (mm)	400	410	440
Ángulo del tubo del sillín	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Longitud del tubo superior (mm) (mm)	555 554	572 571	594 593
Longitud del tubo de dirección (mm) (mm)	90	95	105
Ángulo del tubo de dirección	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Inclinación de la horquilla (mm)	44	44	44
Trail (mm) (mm)	116 112	116 112	116 112
Distancia entre ejes (mm) (mm)	1121 1120	1138 1138	1162 1162
Longitud de la vaina (mm) (mm)	437 435	437 435	437 435
Caída del eje de pedalier (mm) (mm)	51 45	51 45	51 45
Stack (mm) (mm)	602 599	607 603	616 612
Reach (mm) (mm)	399 405	415 421	435 440
Altura del suelo al tubo (mm) (mm)	772 778	770 776	765 765
Ancho del manillar (mm) (mm)	780	780	780
Longitud de la potencia (mm) (mm)	60	60	70
Longitud de las bielas (mm) (mm)	165	170	170

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.