



PIQUE ADVANCED SL 3



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Deep Cove/Sea Sparkle
CUADRO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
TIJERA	Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout
AMORTIGUADOR	Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout
COMPONENTES	
MANUBRIO	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Liv XC Pro, silicone
POTENCIA	Giant Integrated XC, alloy XS: 60, S:60mm, M:70mm, L:70mm
POSTE DE ASIENTO	Giant Core dropper, remote XS: 100mm travel / 30.9 x 395mm S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm
ASIENTO	Liv Grit
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore mechanical, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano Deore
FRENOS	Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano BL-MT501
CASSETTE	Shimano M6100, 10x51
CADENA	KMC X-12
MULTIPLICACIÓN	Praxis Cadet HD M24, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
EJE DE CENTRO	Praxis, press fit

RUEDAS	
RUEDAS	Giant XCA WheelSystem
MAZAS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAYOS	Sapim
NEUMÁTICOS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Precio: \$99,990.00

GEOMETRÍA

CUADRO	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	400		410		440		470	
Ángulo de la Base del Poste de Asiento	75.5°	76.0°	75.5°	76.0°	75.5°	76.0°	75.5°	76.0°
Longitud del Tubo Superior (mm)	555	554	572	571	594	593	611	610
Longitud del Telescopio (mm)	90		95		105		115	
Ángulo del Telescopio	66.5°	67.0°	66.5°	67.0°	66.5°	67.0°	66.5°	67.0°
Rake (mm)	44		44		44		44	
Trail (mm)	116	112	116	112	116	112	116	112
Distancia entre Ejes (mm)	1121	1120	1138	1138	1162	1162	1181	1180
Longitud de Vaina Inferior (mm)	437	435	437	435	437	435	437	435
Caída del Eje de Centro (mm)	51	45	51	45	51	45	51	45
Stack (mm)	602	599	607	603	616	612	625	622
Reach (mm)	399	405	415	421	435	440	450	455
Altura del Tubo Superior al Suelo (mm)	772	778	770	776	765	765	759	765
Ancho del Manubrio (mm)	780		780		780		780	
Longitud de la Potencia (mm)	60		60		70		70	
Longitud de la Biela (mm)	165		170		170		170	

Todas las especificaciones están sujetas a cambios sin previo aviso.