# PIQUE ADVANCED SL 3




## SPECS

| CADRU | |
|---|---|
| **MARIMI** | XS, S, M, L |
| **CULORI** | Deep Cove/Sea Sparkle |
| **CADRU** | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle |
| **FURCA** | Fox 34 SL Performance, 120mm, GRIP damper, Boost 15x110, 44mm offset, remote lockout |
| **SOC** | Fox Float SL Performance Elite, 3-position damper, 210/50, 3-position lockout |
| **COMPONENTE** | |
| **GHIDON** | Giant Integrated XC, alloy, 780mm, 9-degree upsweep |
| **GRIPS** | Liv XC Pro, silicone |
| **PIPA** | Giant Integrated XC, alloy XS: 60, S:60mm, M:70mm, L:70mm |
| **TIJA SA** | Giant Core dropper, remote XS: 100mm travel / 30.9 x 395mm S: 100mm travel / 30.9 x 395mm M: 120mm travel / 30.9 x 395mm |
| **SA** | Liv Grit |
| **PEDALE** | N/A |
| **SISTEMUL DE SCHIMBARE A VITEZELOR** | |
| **MANETE SCHIMBATOR** | Shimano Deore mechanical, 1x12 |
| **SCHIMBATOR FATA** | N/A |
| **SCHIMBATOR SPATE** | Shimano Deore |
| **FRANE** | Shimano BR-MT500, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm |
| **MANETE FRANA** | Shimano BL-MT501 |
| **PINIOANE** | Shimano M6100, 10x51 |
| **LANT** | KMC X-12 |
| **ANGRENAJ** | Praxis Cadet HD M24, 32t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm |
| **BOTTOM BRACKET** | Praxis, press fit |

| ROTI | |
|---|---|
| **JANTE** | Giant XCA WheelSystem |
| **BUTUCI** | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt |
| **SPITE** | Sapim |
| **ANVELOPE** | Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless |
| **EXTRAS** | tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide |

## GEOMETRIE

| CADRU | XS | S | M | L |
|---|---|---|---|---|
| | LOW \| HIGH | LOW \| HIGH | LOW \| HIGH | LOW \| HIGH |
| Seat Tube Length (mm) | 400 | 410 | 440 | 470 |
| Seat Tube Angle | 75,5° \| 76,0° | 75,5° \| 76,0° | 75,5° \| 76,0° | 75,5° \| 76,0° |
| Top Tube Length (mm) | 555 \| 554 | 572 \| 571 | 594 \| 593 | 611 \| 610 |
| Head Tube Length (mm) | 90 | 95 | 105 | 115 |
| Head Tube Angle | 66,5° \| 67,0° | 66,5° \| 67,0° | 66,5° \| 67,0° | 66,5° \| 67,0° |
| Fork Rake (mm) | 44 | 44 | 44 | 44 |
| Trail (mm) | 116 \| 112 | 116 \| 112 | 116 \| 112 | 116 \| 112 |
| Wheelbase (mm) | 1121 \| 1120 | 1138 \| 1138 | 1162 \| 1162 | 1181 \| 1180 |
| Chain Stay Length (mm) | 437 \| 435 | 437 \| 435 | 437 \| 435 | 437 \| 435 |
| Bottom Bracket Drop (mm) | 51 \| 45 | 51 \| 45 | 51 \| 45 | 51 \| 45 |
| Stack (mm) | 602 \| 599 | 607 \| 603 | 616 \| 612 | 625 \| 622 |
| Reach (mm) | 399 \| 405 | 415 \| 421 | 435 \| 440 | 450 \| 455 |
| Stand Over Height (mm) | 772 \| 778 | 770 \| 776 | 765 \| 765 | 759 \| 765 |
| Handlebar Width (mm) | 780 | 780 | 780 | 780 |
| Stem Length (mm) | 60 | 60 | 70 | 70 |
| Crank Length (mm) | 165 | 170 | 170 | 170 |

*Toate specificatiile enumerate se pot schimba fara notificare prealabila.*