PIQUE ADVANCED SL FRAMESET



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Nebula/Black
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	N/A
SHOCK	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STEM	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
SEATPOST	N/A

WHEELS	
EXTRAS	2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

GEOMETRY

FRAME	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	400	410	440	470
Seat Tube Angle	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Top Tube Length (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Wheelbase (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Chain Stay Length (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Reach (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Stand Over Height (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	170

All specifications listed are subject to change without notice.