PIQUE ADVANCED SL FRAMESET



SPECS

CADRU	
MARIMI	XS, S, M, L
CULORI	Nebula/Black
CADRU	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FURCA	N/A
SOC	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
COMPONENTE	
GHIDON	Giant Integrated XC, composite, 780mm, 9-degree upsweep
PIPA	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
TIJA SA	N/A

ROTI	
EXTRAS	2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

GEOMETRIE

CADRU	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	400	410	440	470
Seat Tube Angle	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Top Tube Length (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Wheelbase (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Chain Stay Length (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Reach (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Stand Over Height (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	170

Toate specificatiile enumerate se pot schimba fara notificare prealabila.