PIQUE ADVANCED SL SE



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Stella Purple/Electric Rose
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FORK	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
SHOCK	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Liv XC Pro, silicone
STEM	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
SEATPOST	RockShox Reverb AXS, pod controller remote XS: 100mm travel / 30.9 x 395mm S: 100mm travel / 30.9 x 395mm M: 100mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 3
SADDLE	Liv Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XX SL Eagle Transmission
BRAKES	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BRAKE LEVERS	SRAM Motive ULT
CASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
CHAIN	SRAM XX SL Eagle Transmission
CRANKSET	SRAM XX SL Eagle Transmission with Quark power meter, 32t, 55mm chainline XS: 165mm S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	XCR 29 carbon wheelsystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPOKES	Carbon
TIRES	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Suggested Retail Price (CDN): $15,299.00

FRAME GEOMETRY

FRAME	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	400	410	440	470
Seat Tube Angle	75.5° | 76.0°	75.5° | 76.0°	75.5° | 76.0°	75.5° | 76.0°
Top Tube Length (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.5° | 67.0°	66.5° | 67.0°	66.5° | 67.0°	66.5° | 67.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Wheelbase (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Chain Stay Length (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Reach (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Stand Over Height (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	170

All prices and specifications are subject to change without notice.