

PIQUE ADVANCED SL SE



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Stella Storm
FRAME	Advanced SL-grade composite front and rear triangles, 120 mm FlexPoint Pro suspension, flip chip, 12x148 mm thru-axle
FORK	RockShox SID Ultimate Flight Attendant, 120 mm, Flight Attendant Race Day damper, 15 x 110 mm BOOST, 44mm offset, custom decals
SHOCK	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210 x 50 mm, custom decals
COMPONENTS	
HANDLEBAR	Giant Contact SLR XC Integrated, composite, 780 mm, 9° backsweep, 2° upsweep
GRIPS	Liv XC Pro, silicone
STEM	"Giant Contact SLR XC Integrated, composite XS: 60 mm, S: 60 mm, M: 70 mm, L: 70 mm"
SEATPOST	"RockShox Reverb AXS, pod controller remote XS: 100 mm travel / 30.9 x 395 mm S: 100 mm travel / 30.9 x 395 mm M: 100 mm travel / 30.9 x 395 mm L: 125 mm travel / 30.9 x 395 mm"
SADDLE	Liv Grit SLR
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod Rocker Controller, MMX, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XX SL Eagle Transmission
BRAKES	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors, [F] 180 mm, [R] 160 mm, custom caliper graphics
BRAKE LEVERS	SRAM Motive ULT, custom graphics
CASSETTE	SRAM XS-1299 Eagle Transmission, 10-52T
CHAIN	SRAM XX SL Eagle Transmission
CRANKSET	"SRAM XX SL Eagle Transmission with Quarq power meter, 32T, 55 mm chainline XS: 165 mm S: 170 mm, M: 170 mm, L: 170 mm"
BOTTOM BRACKET	SRAM DUB, press-fit

WHEELS	
RIMS	CADEX Max XC WheelSystem, 30 mm inner width
HUBS	"[F] CADEX Max XC, CenterLock, one-piece integrated hub and spokes [R] CADEX Max XC M1-C120, 120T Helical-Bevel Ratchet Driver, CADEX Wave Spring, CenterLock, one-piece integrated hub and spokes"
SPOKES	CADEX Super Aero carbon with lightweight titanium thread
TIRES	Maxxis Aspen [F/R], 29 x 2.4 in, foldable, 120 TPI, MaxxSpeed, EXO, tubeless
EXTRAS	Tubeless prepared, 2.4 in max tire size, 34T max chainring size, MRP SL TR2 chain guide, top-cap computer mount

Suggested Retail Price (CDN): \$16,499.00

FRAME GEOMETRY

FRAME	XS	S	M
	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	410	440
Seat Tube Angle	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Top Tube Length (mm)	555 554	572 571	594 593
Head Tube Length (mm)	90	95	105
Head Tube Angle	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Fork Rake (mm)	44	44	44
Trail (mm)	116 112	116 112	116 112
Wheelbase (mm)	1121 1120	1138 1138	1162 1162
Chain Stay Length (mm)	437 435	437 435	437 435
Bottom Bracket Drop (mm)	51 45	51 45	51 45
Stack (mm)	602 599	607 603	616 612
Reach (mm)	399 405	415 421	435 440
Stand Over Height (mm)	772 778	770 776	765 765
Handlebar Width (mm)	780	780	780
Stem Length (mm)	60	60	70
Crank Length (mm)	165	170	170

All prices and specifications are subject to change without notice.