PIQUE ADVANCED SL SE



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Stella Purple/Electric Rose
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GABEL	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
DÄMPFER	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
KOMPONENTEN	
LENKER	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIFFE	Liv XC Pro, silicone
VORBAU	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
SATTELSTÜTZE	RockShox Reverb AXS, pod controller remote XS: 100mm travel / 30.9 x 395mm S: 100mm travel / 30.9 x 395mm M: 100mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 3
SATTEL	Liv Grit SL
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM XX SL Eagle Transmission
BREMSEN	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BREMSHEBEL	SRAM Motive ULT
KASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
KETTE	SRAM XX SL Eagle Transmission
KURBEL	SRAM XX SL Eagle Transmission with Quark power meter, 32t, 55mm chainline XS: 165mm S:170mm, M:170mm, L:170mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	XCR 29 carbon wheelsystem
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPEICHEN	Carbon
REIFEN	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Sitzrohrlänge (mm)	400	410	440	470
Sitzrohrwinkel	75.5° | 76.0°	75.5° | 76.0°	75.5° | 76.0°	75.5° | 76.0°
Oberrohrlänge (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	66.5° | 67.0°	66.5° | 67.0°	66.5° | 67.0°	66.5° | 67.0°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Radstand (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Kettenstreben-Länge (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Tretlager-Höhe (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Reach (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Überstandshöhe (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	60	60	70	70
Kurbellänge (mm)	165	170	170	170

Spezifikations-, Preis- und Farbänderungen vorbehalten.