PIQUE ADVANCED SL SE



SPECS

CADRU	
MARIMI	XS, S, M, L
CULORI	Stella Purple/Electric Rose
CADRU	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FURCA	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
SOC	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPONENTE	
GHIDON	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Liv XC Pro, silicone
PIPA	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
TIJA SA	RockShox Reverb AXS, pod controller remote XS: 100mm travel / 30.9 x 395mm S: 100mm travel / 30.9 x 395mm M: 100mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 3
SA	Liv Grit SL
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM AXS Pod, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	SRAM XX SL Eagle Transmission
FRANE	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
MANETE FRANA	SRAM Motive ULT
PINIOANE	SRAM XS 1299 Eagle Transmission, 10x52
LANT	SRAM XX SL Eagle Transmission
ANGRENAJ	SRAM XX SL Eagle Transmission with Quark power meter, 32t, 55mm chainline XS: 165mm S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	XCR 29 carbon wheelsystem
BUTUCI	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPITE	Carbon
ANVELOPE	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

GEOMETRIE

CADRU	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	400	410	440	470
Seat Tube Angle	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°	75,5° | 76,0°
Top Tube Length (mm)	555 | 554	572 | 571	594 | 593	611 | 610
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°	66,5° | 67,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	116 | 112	116 | 112	116 | 112	116 | 112
Wheelbase (mm)	1121 | 1120	1138 | 1138	1162 | 1162	1181 | 1180
Chain Stay Length (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	51 | 45	51 | 45	51 | 45	51 | 45
Stack (mm)	602 | 599	607 | 603	616 | 612	625 | 622
Reach (mm)	399 | 405	415 | 421	435 | 440	450 | 455
Stand Over Height (mm)	772 | 778	770 | 776	765 | 765	759 | 765
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	170

Toate specificatiile enumerate se pot schimba fara notificare prealabila.