PIQUE X ADVANCED SL 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Dune Beige/Raw Carbon
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORK	Fox 34 SL Performance Elite, 130mm, GRIP X damper, Boost 15x110, 44mm offset
SHOCK	Fox Float SL Factory, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Liv Tactal, lock on
STEM	Giant Integrated XC Carbon XS: 50, S:50mm, M:50mm, L:60mm
SEATPOST	Giant Contact Switch AT dropper, remote XS:110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm
SADDLE	Liv Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX AXS Transmission
BRAKES	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XS 1275, 10x52
CHAIN	SRAM GX Transmission
CRANKSET	SRAM GX Transmission, 30t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCR Carbon WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Suggested Retail Price (CDN): $8,699.00

FRAME GEOMETRY

FRAME	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	400	410	440	470
Seat Tube Angle	75.0° | 75.5°	75.0° | 75.5°	75.0° | 75.5°	75.1° | 75.6°
Top Tube Length (mm)	557 | 555	574 | 572	596 | 594	613 | 611
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.0° | 66.5°	66.0° | 66.5°	66.0° | 66.5°	66.1° | 66.6°
Fork Rake (mm)	44	44	44	44
Trail (mm)	119.6 | 115.7	119.5 | 115.7	119.3 | 115.6	119.2 | 115.5
Wheelbase (mm)	1125 | 1124	1143 | 1142	1166 | 1166	1185 | 1184
Chain Stay Length (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	48 | 42	48 | 42	48 | 42	48 | 42
Stack (mm)	605 | 602	610 | 607	620 | 616	629 | 625
Reach (mm)	394 | 400	410 | 416	430 | 436	445 | 450
Stand Over Height (mm)	777 | 784	775 | 782	770 | 777	765 | 771
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	50	50	50	60
Crank Length (mm)	165	170	170	170

All prices and specifications are subject to change without notice.