



PIQUE X ADVANCED SL 2



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	White/Carbon
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORK	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
SHOCK	Fox Float SL Performance, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Liv Tactal, lock on
STEM	Giant Integrated XC, alloy XS: 50, S:50mm, M:50mm, L:60mm
SEATPOST	Giant Contact Switch AT dropper, remote XS:110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm
SADDLE	Giant Grit
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90 mechanical, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 Transmission
BRAKES	Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano SLX BL-M7100
CASSETTE	SRAM 70 1270, 10x52
CHAIN	SRAM 90 Transmission
CRANKSET	SRAM 90 Transmission, 30t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCA WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

Suggested Retail Price (CDN): \$7,499.00

FRAME GEOMETRY

FRAME	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	410	440	470
Seat Tube Angle	75.0° 75.5°	75.0° 75.5°	75.0° 75.5°	75.1° 75.6°
Top Tube Length (mm)	557 555	574 572	596 594	613 611
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.0° 66.5°	66.0° 66.5°	66.0° 66.5°	66.1° 66.6°
Fork Rake (mm)	44	44	44	44
Trail (mm)	119.6 115.7	119.5 115.7	119.3 115.6	119.2 115.5
Wheelbase (mm)	1125 1124	1143 1142	1166 1166	1185 1184
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	48 42	48 42	48 42	48 42
Stack (mm)	605 602	610 607	620 616	629 625
Reach (mm)	394 400	410 416	430 436	445 450
Stand Over Height (mm)	777 784	775 782	770 777	765 771
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	50	50	50	60
Crank Length (mm)	165	170	170	170

All prices and specifications are subject to change without notice.