

# PIQUE X ADVANCED SL 2



## SPECS

FRAME	
SIZES	XS, S, M
COLORS	White/Carbon
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORK	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
SHOCK	Fox Float SL Performance
COMPONENTS	
HANDLEBAR	Giant Integrated XC, alloy, 9-degree upsweep
GRIPS	Giant Tactal Single lock-on
STEM	Giant Integrated XC Alloy XS:50mm, S:50mm, M:50mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.
SADDLE	Liv Grit
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 T-Type
BRAKES	Shimano SLX BR-M7120 4 piston, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano SLX BR-M7100
CASSETTE	SRAM XS-1270, T-Type 10x52
CHAIN	SRAM Eagle 70 T-Type
CRANKSET	SRAM Eagle 90 T-Type, 32t, 55mm chainline XS:165mm, S:170mm, M:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	XCA 29 Alloy Wheelsystem
HUBS	[F] Giant alloy, 6-bolt [R] Giant Alloy, 120T Helical-Bevel Ratchet Driver, 6-Bolt
SPOKES	Sapim
TIRES	[F] Maxxis Rekon 29x2.4", TLR, EXO, tubeless, [R] Maxxis Rekon Race 29x2.4", TLR, EXO, tubeless
EXTRAS	Tubeless prepared, 2.4" max tyre size, 34t max chainring size, MRP 1x CS chain guide

**Price: \$9,299.00**

## GEOMETRY

FRAME	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	410	440	470				
Seat Tube Angle	75.0°   75.5°	75.0°   75.5°	75.0°   75.5°	75.1°   75.6°				
Top Tube Length (mm)	557   555	574   572	596   594	613   611				
Head Tube Length (mm)	90	95	105	115				
Head Tube Angle	66.0°   66.5°	66.0°   66.5°	66.0°   66.5°	66.1°   66.6°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	119.6   115.7	119.5   115.7	119.3   115.6	119.2   115.5				
Wheelbase (mm)	1125   1124	1143   1142	1166   1166	1185   1184				
Chain Stay Length (mm)	437   435	437   435	437   435	437   435				
Bottom Bracket Drop (mm)	48   42	48   42	48   42	48   42				
Stack (mm)	605   602	610   607	620   616	629   625				
Reach (mm)	394   400	410   416	430   436	445   450				
Stand Over Height (mm)	777   784	775   782	770   777	765   771				
Stem Length (mm)	50	50	50	60				
Crank Length (mm)	165	170	170	170				

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.