엔비리브 어드밴스 PRO 1 AXS



스펙

프레임	
사이즈	XXS, XS, S, M, L
색상	Supernova Grey
프레임	Advanced-grade composite, 12x142mm thru-axle, disc
포크	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
부품	
핸들바	Liv Contact SLR 1 Aero Integrated, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIPS	Liv Stratus Lite 2.0
스템	Liv Contact SLR 1 Aero Integrated, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
싯포스트	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
안장	Liv Alacra SL
구동계	
변속기	SRAM Rival AXS E1
앞 변속기	SRAM Rival AXS E1
뒷 변속기	SRAM Rival AXS E1
브레이크	SRAM Rival E1 hydraulic, SRAM PaceLine rotors [F] 160mm, [R] 140mm
브레이크 레버	SRAM Rival AXS E1
스프라켓	SRAM Rival E1, 12-speed, 10x36
체인	SRAM Rival E1
크랭크 셋	SRAM Rival E1, 35/48 with power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
BB	SRAM DUB, press fit

바퀴	
림	Giant SLR 1 50 Carbon Disc WheelSystem, [F] 50mm, [R] 50mm
허브	[F] Giant Aero Hub, CenterLock, 12mm thru-axle [R] Giant Aero Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
스포크	Sapim CX-Ray
타이어	Giant Gavia Course, 700x28c, folding, tubeless
추가 기능	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

가격: ₩6,990,000

지오메트리

프레임	XXS	XS	S
시트 튜브 길이 (mm)	446.5	465	498
시트 튜브 각도	75.0°	75.0°	74.5°
탑튜브 길이 (mm)	504	514.8	526.2
헤드 튜브 길이 (mm)	100	115	130
헤드튜브 각도	70.0°	71.0°	72.0°
포크 레이크 (mm)	49	49	49
트레일 (mm)	73.2	66.8	60.4
휠베이스 (mm)	969.9	974.7	977
체인스테이 길이 (mm)	405	405	405
BB (mm)	72	72	70
스택 (mm)	494.1	511.8	527
범위 (mm)	365.6	372.9	377.8
스탠드 오버 (mm)	714.8	732.6	760.8
핸들바 폭 (mm)	360	380	380
스템 길이 (mm)	80	80	90
크랭크 길이 (mm)	160	165	165

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.