



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Desert Sage
FRAME	ALUXX-grade aluminum, disc
VOORVORK	SR Suntour NEX HLO 700C, 63mm, disc, lockout without rebound
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Connect XC, 31.8mm, 9-degree/6-degree rise XS: 640mm, S: 640mm, M: 680mm, L: 680mm
HANDVATTEN	Liv ErgoContact
STUURPEN	Giant Sport XS: 70mm, S: 80mm, M: 80mm, L: 90mm
ZADEL	Liv Ergo Contact
PEDALEN	platform
AFMONTAGE	
SHIFTERS	Shimano CUES, 2x10
VOORDERAILLEUR	Shimano CUES
ACHTERDERAILLEUR	Shimano CUES
REMMEN	Tektro TKD143, hydraulic disc [F]160mm, [R]160mm
REMHENDELS	Tektro TKD149
CASSETTE	Shimano CSLG40010D, 11x39
AANDRIJVING	KMC X11 with Missing Link
CRANKSET	Shimano CUES, forged alloy, 30/46 XS: 170mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	threaded

WIELSET	
VELGEN	Giant SX Disc
NAVEN	alloy, 28h
SPAKEN	stainless steel, 14g
BANDEN	Giant CrossCut, 700x42c, puncture protect
EXTRA'S	55c max tire size without fender, 45c max tire size with fender, reflective stickers, kickstand, fender and rack frame mounts

Adviesprijs: € 999,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis lengte (mm)	380	420	460	500
Zitbuis hoek	74,0°	73,5°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	550	570	590	610
Balhoofdbuis Lengte (mm)	110	120	135	150
Balhoofdbuis Hoek	70,5°	70,5°	70,5°	70,5°
Vork Sprong (mm)	42	42	42	42
Naloop (mm)	85,1	85,1	85,1	85,1
Wielbasis (mm)	1059	1074	1089	1109
Liggende achtervork lengte (mm)	450	450	450	450
Bottom Bracket Drop (mm)	62	62	62	62
Stack (mm)	601	611	625	639
Reach (mm)	378	389	399	415
Stand Over Height (mm)	589	606	619	629
Stuur breedte (mm)	640	640	680	680
Stuurpen Lengte (mm)	70	80	80	90
Cranklengte (mm)	165	170	170	175
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.