



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Core, 50Nm, Power by Yamaha
CONTROLLER	RideControl One Ant+
DISPLAY	RideDash Plus (optional)
BATTERY	EnergyPak 400, 36V 11.6Ah Rechargeable Lithium-Ion
FRAME	
SIZES	XS, S, M
COLOURS	Laurel
FRAME	ALUXX Aluminium, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
FORK	SR Suntour NEX E25 63mm travel
SHOCK	-
COMPONENTS	
HANDLEBAR	Giant Connect Riser
GRIPS	Liv Comfort Ergo Microtech Plus
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Liv Comfort
PEDALS	Aluminium Platform
DRIVETRAIN	
SHIFTERS	Microshift Advent
FRONT DERAILLEUR	-
REAR DERAILLEUR	Microshift Advent, 9-speed
BRAKES	Tektro HD-M275, hydraulic disc, 160/180mm
BRAKE LEVERS	Tektro HD-M275
CASSETTE	Microshift Advent, 11-42T, 9-speed
CHAIN	KMC X9
CRANKSET	Forged Alloy minimal Q-factor, 42T
BOTTOM BRACKET	-

WHEELS	
RIMS	Liv GX03V, 700C Aluminium
HUBS	Giant eTracker, [F] 100x9mm QR [R] 135mm QR
SPOKES	Stainless steel
TIRES	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready W/O Reflex (GU: w/reflex)
EXTRAS	-
ACCESSORIES	
LIGHTING	-
LOCK	-
CARRIER	-

Price: \$3,399.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	370	420	470
Seat Tube Angle	74.0°	73.5°	73.5°
Top Tube Length (mm)	545	565	585
Head Tube Length (mm)	135	135	155
Head Tube Angle	69.5°	69.5°	69.5°
Fork Rake (mm)	42	42	42
Trail (mm)	91.3	91.3	91.3
Wheelbase (mm)	1097	1111	1133
Chain Stay Length (mm)	470	470	470
Bottom Bracket Drop (mm)	60	60	60
Stack (mm)	619	619	638
Reach (mm)	367	382	396
Stand Over Height (mm)	616	596	584
Stem Length (mm)	70	80	80
Crank Length (mm)	170	170	170
Wheel Size	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.