디보트 어드밴스 SL 1



스펙

프레임	
사이즈	XS, S, M, L
색상	Ember Violet
프레임	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
포크	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
부품	
핸들바	Liv Contact SLR XR Integrated XS: 380/420mm, S: 380/420mm, M: 380/420mm, L: 400/440mm
GRIPS	Liv Stratus Elite 3.0
스템	Liv Contact SLR XR Integrated XS: 60mm, S: 70mm, M: 80mm, L: 100mm
싯포스트	Giant Contact SLR XR D-Fuse, composite, 20mm offset
안장	Liv Grit SLR
구동계	
변속기	SRAM Force XPLR AXS E1, 1x13
뒷 변속기	SRAM Force XPLR AXS E1
브레이크	SRAM Force AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
브레이크 레버	SRAM Force E1 hydraulic
스프라켓	SRAM Force E1, 13-speed, 10x46
체인	SRAM Force E1
크랭크 셋	SRAM Force XPLR AXS with power meter, 40t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BB	SRAM DUB, press fit

바퀴	
림	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
허브	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
스포크	Aero Bladed Carbon Spoke
타이어	CADEX GXR, 700x45c, tubeless
추가 기능	tubeless prepared, computer mount, chain guide
LIMITS	
최대 타이어 클리어런스	53mm max tire size
최대 체인링 사이즈	54t max chainring size

가격: ₩9,990,000

지오메트리

프레임	XS	S
시트 튜브 길이 (mm)	390	420
시트 튜브 각도	75.0°	74.5°
탑튜브 길이 (mm)	528	538
헤드 튜브 길이 (mm)	90	100
헤드튜브 각도	70.5°	71.0°
포크 레이크 (mm)	50	50
트레일 (mm)	75	72
휠베이스 (mm)	1024	1025
체인스테이 길이 (mm)	433	433
BB (mm)	80	80
스택 (mm)	525	537
범위 (mm)	387	389
스탠드 오버 (mm)	663	714
핸들바 폭 (mm)	420	420
스템 길이 (mm)	60	70
크랭크 길이 (mm)	165	165
휠사이즈	700C	700C

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.