



SPECIFIKACIJE

OKVIR	
VELIČINE	OSFM
BOJE	Soap Suds
OKVIR	ALUXX-grade aluminum, 12x142 mm thru-axle
VILICA	Advanced-grade composite, full-composite OverDrive steerer, 15x110 thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Giant Sport, alloy, 31.8 mm, 600 mm
GRIPS	Giant Junior
LULA VOLANA	forged alloy, 0-degree
CIJEV SJEDALA	alloy, two-bolt, 30.9x260mm
SJEDALO	Liv Grit Core Lite
PEDALE	platform
POGON	
RUČICE MJENJAČA	MicroSHIFT Acolyte, 1x8, quick trigger shifter with small hand ergonomics and indicator with index thumb operation
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	MicroSHIFT Acolyte, super short cage for increased ground clearance with spring lock
KOČNICE	Tektro HD-J2820 hydraulic [F]160 mm, [R]160 mm rotors
RUČICE KOČNICA	Tektro HD-J2820
KAZETA	Shimano CS-H083, 11x38
LANAC	KMC X8.1
POGON	ProWheel forged alloy, 30t, 105 mm
OSOVINA POGONA (BB)	threaded cartridge

KOTAČI	
OBRUČI	Giant TRA 2, 20", alloy
NABE	[F] Giant Tracker, thru-axle, 6-bolt, [R] Giant Tracker, thru-axle, 6-bolt, HG driver body
ŽBICE	stainless, 14g
GUME	Kenda Booster, 20x2.4"

GEOMETRIJA

OKVIR	One Size
Dužina cijevi sjedala (mm)	265
Seat Post Insertion Depth (mm)	200
Kut cijevi sjedala	73,0°
Dužina gornje cijevi (mm)	444
Dužina prednje cijevi (mm)	90
Kut vilice	67,0°
Zakrivljenost vilice (offset) (mm)	40
Staza (mm)	91
Međuosovinski razmak kotača (mm)	821
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	323
Položaj osovine pogona (mm)	50
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	447
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	301
Prekoračna visina (mm)	536
Širina volana (mm)	600
Dužina lule volana (mm)	40
Dužina poluge pedale (mm)	105

Sve navedene specifikacije podložne su promjeni bez prethodne najave.