



SPECS

FRAME	
SIZES	OSFM
COLORS	Soap Suds
FRAME	ALUXX-grade aluminum, 12x142 mm thru-axle
FORK	Advanced-grade composite, full-composite OverDrive steerer, 15x110 thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Sport, alloy, 31.8 mm, 600 mm
GRIPS	Giant Junior
STEM	forged alloy, 0-degree
SEATPOST	alloy, two-bolt, 30.9x260mm
SADDLE	Liv Grit Core Lite
PEDALS	platform
DRIVETRAIN	
SHIFTERS	MicroSHIFT Acolyte, 1x8, quick trigger shifter with small hand ergonomics and indicator with index thumb operation
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	MicroSHIFT Acolyte, super short cage for increased ground clearance with spring lock
BRAKES	Tektro HD-J2820 hydraulic [F]160 mm, [R]160 mm rotors
BRAKE LEVERS	Tektro HD-J2820
CASSETTE	Shimano CS-H083, 11x38
CHAIN	KMC X8.1
CRANKSET	ProWheel forged alloy, 30t, 105 mm
BOTTOM BRACKET	threaded cartridge

WHEELS	
RIMS	Giant TRA 2, 20", alloy
HUBS	[F] Giant Tracker, thru-axle, 6-bolt, [R] Giant Tracker, thru-axle, 6-bolt, HG driver body
SPOKES	stainless, 14g
TIRES	Kenda Booster, 20x2.4"

GEOMETRY

FRAME	One Size
Seat Tube Length (mm)	265
Seat Post Insertion Depth (mm)	200
Seat Tube Angle	73,0°
Top Tube Length (mm)	444
Head Tube Length (mm)	90
Head Tube Angle	67,0°
Fork Rake (mm)	40
Trail (mm)	91
Wheelbase (mm)	821
Chain Stay Length (mm)	323
Bottom Bracket Drop (mm)	50
Stack (mm)	447
Reach (mm)	301
Stand Over Height (mm)	536
Handlebar Width (mm)	600
Stem Length (mm)	40
Crank Length (mm)	105

All specifications listed are subject to change without notice.