



SPECS

RAMME	
STØRRELSE	OSFM
FARGE	Soap Suds
RAMME	ALUXX-grade aluminum, 12x142 mm thru-axle
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 15x110 thru-axle, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Sport, alloy, 31.8 mm, 600 mm
GRIPS	Giant Junior
STYRSTEM	forged alloy, 0-degree
SETEPINNE	alloy, two-bolt, 30.9x260mm
SADEL	Liv Grit Core Lite
PEDALER	platform
DRIVVERK	
GIRHENDLER	MicroSHIFT Acolyte, 1x8, quick trigger shifter with small hand ergonomics and indicator with index thumb operation
FRONTGIR	N/A
BAKGIR	MicroSHIFT Acolyte, super short cage for increased ground clearance with spring lock
BREMSER	Tektro HD-J2820 hydraulic [F]160 mm, [R]160 mm rotors
BREMSEHENDLER	Tektro HD-J2820
KASSETT	Shimano CS-H083, 11x38
KJEDE	KMC X8.1
KRANK	ProWheel forged alloy, 30t, 105 mm
BOTTOM BRACKET	threaded cartridge

HJUL	
FELG	Giant TRA 2, 20", alloy
NAV	[F] Giant Tracker, thru-axle, 6-bolt, [R] Giant Tracker, thru-axle, 6-bolt, HG driver body
EIKE	stainless, 14g
DEKK	Kenda Booster, 20x2.4"

GEOMETRI

RAMME	One Size
Seat Tube Length (mm)	265
Seat Post Insertion Depth (mm)	200
Seat Tube Angle	73,0°
Top Tube Length (mm)	444
Head Tube Length (mm)	90
Head Tube Angle	67,0°
Fork Rake (mm)	40
Trail (mm)	91
Wheelbase (mm)	821
Chain Stay Length (mm)	323
Bottom Bracket Drop (mm)	50
Stack (mm)	447
Reach (mm)	301
Stand Over Height (mm)	536
Handlebar Width (mm)	600
Stem Length (mm)	40
Crank Length (mm)	105

Alle spesifikasjonene kan endres uten varsel.