



SPECIFIKACIJE

OKVIR	
VELIKOSTI	OSFM
BARVE	Soap Suds
OKVIR	ALUXX-grade aluminum, 12x142 mm thru-axle
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 15x110 thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Sport, alloy, 31.8 mm, 600 mm
GRIPS	Giant Junior
OPORA KRMILA	forged alloy, 0-degree
OPORA SEDEŽA	alloy, two-bolt, 30.9x260mm
SEDEŽ	Liv Grit Core Lite
PEDALA	platform
POGON	
PRESTAVNE ROČICE	MicroSHIFT Acolyte, 1x8, quick trigger shifter with small hand ergonomics and indicator with index thumb operation
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	MicroSHIFT Acolyte, super short cage for increased ground clearance with spring lock
ZAVORE	Tektro HD-J2820 hydraulic [F]160 mm, [R]160 mm rotors
ZAVORNE ROČICE	Tektro HD-J2820
VERIŽNIK	Shimano CS-H083, 11x38
VERIGA	KMC X8.1
GONILKE Z VERIŽNIKI	ProWheel forged alloy, 30t, 105 mm
BOTTOM BRACKET	threaded cartridge

OBROČNIKI	
OBROČI	Giant TRA 2, 20", alloy
PESTA	[F] Giant Tracker, thru-axle, 6-bolt, [R] Giant Tracker, thru-axle, 6-bolt, HG driver body
NAPERE	stainless, 14g
PLAŠČI	Kenda Booster, 20x2.4"

GEOMETRIJA

OKVIR	One Size
Dolžina sedežne cevi (mm)	265
Seat Post Insertion Depth (mm)	200
Kot sedežne cevi	73,0°
Top Tube Length (mm)	444
Višina glave okvirja (mm)	90
Krmilni kot	67,0°
Zamik vpetja osi (mm)	40
Trail (mm)	91
Medosna razdalja (mm)	821
Dolžina cevi ob verigi (mm)	323
Bottom Bracket Drop (mm)	50
Oddaljenost zgornje cevi od gonilne osi (mm)	447
Doseg (mm)	301
Višina zgornje cevi (mm)	536
Širina krmila (mm)	600
Dolžina opore krmila (mm)	40
Dolžina gonilke (mm)	105

Vse navedene specifikacije se lahko spremenijo brez obvestila.