STP 24 LIV

SPECS

FRAME	
SIZES	OSFM
COLORS	Alpine Green
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle
FORK	Giant Crest TR Comp Lite, 34 mm stanchions, 15x110 mm thru-axle, 100 mm travel, youth tuned
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Sport, alloy, 31.8 mm, 640 mm
GRIPS	Giant Junior
STEM	forged alloy, 0-degree
SEATPOST	Giant Contact Switch AT Lite, remote, 70-100 mm travel, 30.9 mm x 315 mm
SADDLE	Liv Grit Core Lite
PEDALS	platform
DRIVETRAIN	
SHIFTERS	MicroSHIFT Advent, 1x9, quick trigger shifter with small hand ergonomics and indicator with index thumb operation
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	MicroSHIFT Advent, super short cage for increased ground clearance with clutch
BRAKES	Tektro HD-J2820 hydraulic [F]180mm, [R]160mm rotors
BRAKE LEVERS	Tektro HD-J2820
CASSETTE	Shimano CS-H093, 11x38
CHAIN	KMC X9
CRANKSET	alloy forged, 30t, 140mm
BOTTOM BRACKET	threaded cartridge

WHEELS	
RIMS	Giant TRA 2, 24", alloy
HUBS	[F] Giant Tracker, thru-axle, 6-bolt [R] Giant Tracker thru-axle, 6-bolt, HG driver body
SPOKES	stainless, 14g
TIRES	Kenda Amrak, 24x2.2"

GEOMETRY

FRAME	One Size
Seat Tube Length (mm)	300
Seat Post Insertion Depth (mm)	250
Seat Tube Angle	73,0°
Top Tube Length (mm)	523
Head Tube Length (mm)	90
Head Tube Angle	67,0°
Fork Rake (mm)	30
Trail (mm)	104
Wheelbase (mm)	975
Chain Stay Length (mm)	375
Bottom Bracket Drop (mm)	40
Stack (mm)	534
Reach (mm)	360
Stand Over Height (mm)	629
Handlebar Width (mm)	640
Stem Length (mm)	40
Crank Length (mm)	140

All specifications listed are subject to change without notice.