

STP 26 LIV



SPECS

FRAME	
SIZES	OSFM
COLOURS	Quicksilver
FRAME	ALUXX-grade aluminum, 10x135 mm closed horizontal dropouts
FORK	Marzocchi Bomber DJ, 36 mm stanchions, GRIP damper, 20x110 mm, 100 mm travel
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 760 mm, 35 mm rise
GRIPS	Giant Tactal Pro, lock on
STEM	Giant Contact 35 DJ, 0-degree, 35 mm
SEATPOST	alloy, two-bolt, 30.9 x 260 mm
SADDLE	Liv Ergo Contact Trail
PEDALS	platform
DRIVETRAIN	
BRAKES	[F] mechanical disc, [R] Shimano MT500, hydraulic disc TR-55 [F]180 mm, [R]160 mm rotors
BRAKE LEVERS	Shimano BL-MT501
CASSETTE	13t, stainless steel
CHAIN	KMC Z1 wide
CRANKSET	Prowheel forged, alloy, 30t, 165 mm
BOTTOM BRACKET	73mm, threaded

WHEELS	
RIMS	Giant TRA 2, 26", alloy
HUBS	Giant Disc, 32h, [F] 20x110 [R] 10x135 thru-axle, alloy, disc
SPOKES	stainless, 14g
TIRES	Kenda Booster, 26x2.25"

Suggested Retail Price (CDN): \$2,149.00

FRAME GEOMETRY

FRAME	One Size
Seat Tube Length (mm)	310
Seat Post Insertion Depth (mm)	225
Seat Tube Angle	72.0°
Top Tube Length (mm)	594
Head Tube Length (mm)	120
Head Tube Angle	68.5°
Fork Rake (mm)	37
Trail (mm)	95
Wheelbase (mm)	1047
Chain Stay Length (mm)	385
Bottom Bracket Drop (mm)	25
Stack (mm)	566
Reach (mm)	410
Stand Over Height (mm)	672
Handlebar Width (mm)	760
Stem Length (mm)	35
Crank Length (mm)	165

All prices and specifications are subject to change without notice.