

TEMPT 1



SPECS

FRAME	
SIZES	XS, S, M, L
FRAME	ALUXX-grade aluminum, disc
FORK	GIANT SXC32-2 RCL Alloy SingleAir 29"/27.5" 15x110 TA XS: 80mm (27.5") Spring: Air, S: 80mm (27.5"), 100mm(29") Spring: Air, M: 100mm(29") Spring: Air, L: 100mm(29") Spring: Air
COMPONENTS	
HANDLEBAR	Giant Connect Trail 690mm, 31.8 XS: 690(27.5"), S: 690(27.5") 750 (29"), M: 750(29"), L: 750(29")
GRIPS	Sole-O Grip
STEM	Giant Sport Alloy 7 Degree XS: 40 (27.5"), S: 40(27.5"/29"), M: 50(29"), L: 50(29")
SEATPOST	Giant Sport 30.9, XS: 350(27.5"), S: 350(27.5") / 375(29"), M: 375(29"), L: 375(29")
SADDLE	Contact ergo
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	Microshift Advent MX 1x11 SL-M7115-R
REAR DERAILLEUR	Microshift Advent 1x11 RD-M7015M
BRAKES	Tektro HD-M3121, Hydraulic, [F] 180mm [R] 160mm
BRAKE LEVERS	Tektro HD-M3121
CASSETTE	Microshift Advent MX 1x11 CS-H114 11-50T
CHAIN	KMC X11
CRANKSET	ProWheel Charm Steel, 52.5mm chainline, 32t (27.5"), 30t w/O Chain Guard for (29") XS: 165mm(27.5"), S: 165mm(27.5")/170mm(29"), M: 170mm(29"), L: 170mm(29")
BOTTOM BRACKET	FP-B902W

WHEELS	
RIMS	Giant GX03V 27.5"/29" 6061 Aluminum, Double Wall, 21mm Inner Width, Disc, 28h
HUBS	alloy, sealed bearing
SPOKES	Stainless 14G
TIRES	Maxxis Rekon Race 29x2.4" Rekon 27.5x2.4" 60 TPI wire bead
LIMITS	
MAX TIRE CLEARANCE	29X2.4"
MAX CHAINRING SIZE	32T

Recommended Retail Price: \$1,000.00

GEOMETRY

FRAME	XS (27.5")	S (29")	M (29")	L (29")
Seat Tube Length (inch)	13	15	16.1	17.3
Seat Post Insertion Depth (inch)	11	13	14.2	8.7
Seat Tube Angle	74.0°	74.5°	74.5°	74.5°
Top Tube Length (inch)	21.2	22.5	23.6	24.8
Head Tube Length (inch)	3.5	3.5	3.9	4.7
Head Tube Angle	67.0°	67.5°	67.5°	67.5°
Fork Rake (inch)	1.7	1.7	1.7	1.7
Trail (inch)	4.1	4.3	4.3	4.3
Wheelbase (inch)	42.5	44.4	45.6	46.9
Chain Stay Length (inch)	17.3	17.9	17.9	17.9
Bottom Bracket Drop (inch)	1.8	2.2	2.2	2.2
Stack (inch)	21.6	23.3	23.7	24.4
Reach (inch)	15	16	17	18
Stand Over Height (inch)	26.8	27.1	27.9	
Handlebar Width (inch)	27.2	27.2	27.2	29.9
Stem Length (inch)	1.6	1.6	2	2.4
Crank Length (inch)	6.5	6.7	6.7	6.7

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*