

TEMPT 1



SPECS

FRAME	
SIZES	XS, S, M, L
FRAME	ALUXX-grade aluminum, disc
FORK	GIANT SXC32-2 RCL Alloy SingleAir 29"/27.5" 15x110 TA XS: 80mm (27.5") Spring: Air, S: 80mm (27.5"), 100mm(29") Spring: Air, M: 100mm(29") Spring: Air, L: 100mm(29") Spring: Air
COMPONENTS	
HANDLEBAR	Giant Connect Trail 690mm, 31.8 XS: 690(27.5"), S: 690(27.5") 750 (29"), M: 750(29"), L: 750(29")
GRIPS	Sole-O Grip
STEM	Giant Sport Alloy 7 Degree XS: 40 (27.5"), S: 40(27.5"/29"), M: 50(29"), L: 50(29")
SEATPOST	Giant Sport 30.9, XS: 350(27.5"), S: 350(27.5") / 375(29"), M: 375(29"), L: 375(29")
SADDLE	Contact ergo
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	Microshift Advent MX 1x11 SL-M7115-R
REAR DERAILLEUR	Microshift Advent 1x11 RD-M7015M
BRAKES	Tektro HD-M3121, Hydraulic, [F] 180mm [R] 160mm
BRAKE LEVERS	Tektro HD-M3121
CASSETTE	Microshift Advent MX 1x11 CS-H114 11-50T
CHAIN	KMC X11
CRANKSET	ProWheel Charm Steel, 52.5mm chainline, 32t (27.5"), 30t w/O Chain Guard for (29") XS: 165mm(27.5"), S: 165mm(27.5")/170mm(29"), M: 170mm(29"), L: 170mm(29")
BOTTOM BRACKET	FP-B902W

WHEELS	
RIMS	Giant GX03V 27.5"/29" 6061 Aluminum, Double Wall, 21mm Inner Width, Disc, 28h
HUBS	alloy, sealed bearing
SPOKES	Stainless 14G
TIRES	Maxxis Rekon Race 29x2.4" Rekon 27.5x2.4" 60 TPI wire bead
LIMITS	
MAX TIRE CLEARANCE	29X2.4"
MAX CHAINRING SIZE	32T

Suggested Retail Price (CDN): \$1,289.00

FRAME GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Seat Tube Length (mm)	330	365	380	410	440
Seat Post Insertion Depth (mm)	280	310	330	360	220
Seat Tube Angle	74.0°	74.0°	74.5°	74.5°	74.5°
Top Tube Length (mm)	538	558	571	599	629
Head Tube Length (mm)	90	95	90	100	120
Head Tube Angle	67.0°	67.0°	67.5°	67.5°	67.5°
Fork Rake (mm)	44	44	44	44	44
Trail (mm)	105.2	105.2	108.9	108.9	108.9
Wheelbase (mm)	1080	1101	1129	1158	1190
Chain Stay Length (mm)	440	440	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55
Stack (mm)	548	553	593	602	620
Reach (mm)	381	400	407	432	457
Stand Over Height (mm)	680	689	689	708	
Handlebar Width (mm)	690	690	690	690	760
Stem Length (mm)	40	40	40	50	60
Crank Length (mm)	165	165	170	170	170

All prices and specifications are subject to change without notice.