# TEMPT 2




## SPECS

| FRAME | |
|---|---|
| **SIZES** | 27.5": XS, S, 29": S, M, L |
| **COLORS** | Mars Dust, Frost Silver |
| **FRAME** | ALUXX-grade aluminum, disc |
| **FORK** | Giant SXC32-3 RL Coil w/Pre-load Adj & 15x110 TA 1.5" Taper steerer 27.5" XS: 80mm, S: 80mm 29" S: 100mm, M: 100mm, L: 100mm |
| **SHOCK** | N/A |
| **COMPONENTS** | |
| **HANDLEBAR** | Giant Connect Trail, 31.8mm 27.5" XS: 690mm, S: 690mm 29" S: 750mm, M: 750mm, L: 750mm |
| **GRIPS** | Giant Sole-O |
| **STEM** | Giant Sport, 7-degree 27.5" XS: 40mm, S: 40mm 29" S: 40mm, M: 50mm, L: 50 |
| **SEATPOST** | Giant Sport, 30.9mm 27.5" XS:100x350mm, S: 100x350mm 29" S: 100x350mm, M:100x375mm, L : 100x375mm |
| **SADDLE** | Contact Ergo |
| **PEDALS** | MTB caged |
| **DRIVETRAIN** | |
| **SHIFTERS** | Microshift, Advent 1x9, SL-M9295R |
| **FRONT DERAILLEUR** | N/A |
| **REAR DERAILLEUR** | Microshift, Advent 1x9, RD-M6195M with clutch |
| **BRAKES** | Tektro HDC TKD 149, hydraulic, Tektro rotors [F]180mm, [R]160mm |
| **BRAKE LEVERS** | Tektro TKD 149, for small hands |
| **CASSETTE** | Microshift, CS-H093, 11-46 |
| **CHAIN** | KMC X9 |
| **CRANKSET** | ProWheel Charm, steel, 52.5mm chainline 32t (27.5") & 30t (29") 27.5" XS: 165mm, S: 165mm 29" S: 170mm, M: 170mm, L: 170mm |
| **BOTTOM BRACKET** | cartridge |

| WHEELS | |
|---|---|
| **RIMS** | 27.5": Giant GX03V 27.5", alloy, double wall, 21mm inner width 29": Giant GX03V 29", alloy, double wall, 21mm inner width |
| **HUBS** | alloy, sealed bearing |
| **SPOKES** | stainless, 14g |
| **TIRES** | Maxxis Recon Race 27.5x2.4" or 29x2.4", 60tpi wire bead |
| **EXTRAS** | 2.4" max tire size, max chainring 32T |

## GEOMETRY

| FRAME | XS (27.5") | S (27.5") | S (29") | M (29") | L (29") |
|---|---|---|---|---|---|
| Seat Tube Length (mm) | 330 | 365 | 380 | 410 | 450 |
| Seat Post Insertion Depth (mm) | 280 | 310 | 330 | 360 | 220 |
| Seat Tube Angle | 74,0° | 74,0° | 74,5° | 74,5° | 74,0° |
| Top Tube Length (mm) | 538 | 558 | 571 | 599 | 610 |
| Head Tube Length (mm) | 90 | 95 | 90 | 100 | 105 |
| Head Tube Angle | 67,0° | 67,0° | 67,5° | 67,5° | 68,5° |
| Fork Rake (mm) | 44 | 44 | 44 | 44 | 51 |
| Trail (mm) | 105,2 | 105,2 | 108,9 | 108,9 | 94,3 |
| Wheelbase (mm) | 1080 | 1101 | 1129 | 1158 | 1160 |
| Chain Stay Length (mm) | 440 | 440 | 455 | 455 | 455 |
| Bottom Bracket Drop (mm) | 45 | 45 | 55 | 55 | 55 |
| Stack (mm) | 548 | 553 | 593 | 602 | 610 |
| Reach (mm) | 381 | 400 | 407 | 432 | 435 |
| Stand Over Height (mm) | 680 | 689 | 689 | 708 | 757 |
| Handlebar Width (mm) | 690 | 690 | 750 | 750 | 750 |
| Stem Length (mm) | 40 | 40 | 40 | 50 | 50 |
| Crank Length (mm) | 165 | 165 | 170 | 170 | 175 |
| Wheel Size | 27.5" | 27.5" | 29" | 29" | 29" |

*All specifications listed are subject to change without notice.*