

# TEMPT 2 (GE)



## SPECS

FRAME	
<b>SIZES</b>	27.5": XS,S,M 29": S,M,L
<b>COLORS</b>	Ocean Wave
<b>FRAME</b>	ALUXX-Grade Aluminum, disc
<b>FORK</b>	SF22-X1-Coil RLR DS, QR, steel steerer XS: 80mm travel (27.5) S: 100mm travel (27.5) / 100mm travel (29)
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Connect Trail, 31.8mm XS: 670mm (27.5) S: 670mm (27.5) / 670mm (29) M: 750mm (27.5) / 750mm travel (29) L: 750mm (29)
<b>GRIPS</b>	Giant Sole-O
<b>STEM</b>	Giant Sport, 7-degree XS: 40mm (27.5) S: 40mm (27.5) / 40mm (29) M: 50mm (27.5) / 50mm travel (29) L: 50mm (29)
<b>SEATPOST</b>	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (29)
<b>SADDLE</b>	Liv Sport
<b>PEDALS</b>	MTB caged
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Alivio SL-M3100, 2x9
<b>FRONT DERAILLEUR</b>	Shimano Alivio M3120
<b>REAR DERAILLEUR</b>	Shimano Deore M592
<b>BRAKES</b>	Shimano Deore BR-MT200, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano Deore BL-MT200
<b>CASSETTE</b>	Shimano Deore HG200, 11x36
<b>CHAIN</b>	KMC X9
<b>CRANKSET</b>	Shimano MT101-2, 22/36 XS: 170mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 170mm travel (29) L: 175mm (29)
<b>BOTTOM BRACKET</b>	cartridge

WHEELS	
<b>RIMS</b>	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
<b>HUBS</b>	alloy, sealed bearing
<b>SPOKES</b>	stainless, 14g
<b>TIRES</b>	Kenda Booster 27.5 or 29x2.2", wire bead
<b>EXTRAS</b>	2.4" max tire size

## GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Seat Tube Length (mm)	325	365	370	405	420	450
Seat Tube Angle	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	542	571	570	594	590	610
Head Tube Length (mm)	95	100	90	110	95	105
Head Tube Angle	68,0°	68,0°	68,5°	68,0°	68,5°	68,5°
Fork Rake (mm)	40	42	51	42	51	51
Trail (mm)	102	98,9	94,3	98,9	94,3	94,3
Wheelbase (mm)	1072	1104	1119	1128	1139	1160
Chain Stay Length (mm)	440	440	455	440	455	455
Bottom Bracket Drop (mm)	40	45	55	45	55	55
Stack (mm)	554	579	596	588	601	610
Reach (mm)	383	405	399	425	418	435
Stand Over Height (mm)	663	686	705	708	737	757
Handlebar Width (mm)	730	750	750	750	750	750
Stem Length (mm)	40	40	40	50	50	50
Crank Length (mm)	165	165	170	170	170	175
Wheel Size	27.5"	27.5"	29"	27.5"	29"	29"

All specifications listed are subject to change without notice.