

# TEMPT 29/27.5 3 GE



## SPECIFICATIES

FRAME	
MATEN	27.5": XS,S,M 29": S,M,L
KLEUREN	Purple Ash
FRAME	ALUXX-Grade Aluminum, disc
VOORVORK	SR Suntour XCM RL, remote lockout, QR, alloy steerer
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Connect Trail, 31.8mm
HANDVATTEN	Giant Sole-O
STUURPEN	Giant Sport, 7-degree
ZADEL	Giant Sport, 30.9
ZADEL	Liv Sport
PEDALEN	MTB caged
AFMONTAGE	
SHIFTERS	Shimano Altus SL-M2010, 2x9
VOORDERAILLEUR	Shimano Alivio M3120
ACHTERDERAILLEUR	Shimano Alivio M3100
REMMEN	Tektro HDC TKD 149, hydraulic, Tektro rotors [F]180mm, [R]160mm
REMHENDELS	Tektro TKD 149
CASSETTE	Shimano Deore HG200, 11x36
AANDRIJVING	KMC X9
CRANKSET	ProWheel forged, 22/36
BOTTOM BRACKET	cartridge

WIELSET	
VELGEN	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NAVEN	alloy, sealed bearing
SPAKEN	stainless, 14g
BANDEN	Kenda Booster 27.5" or 29x2.2", wire bead
EXTRA'S	2.4" max tire size

Adviesprijs: € 749,00

## GEOMETRIE

FRAME	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Zitbuis lengte (mm)	325	365	370	405	420	450
Zitbuis hoek	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	542	571	570	594	590	610
Balhoofdbuis Lengte (mm)	95	100	90	110	95	105
Balhoofdbuis Hoek	68,0°	68,0°	68,5°	68,0°	68,5°	68,5°
Vork Sprong (mm)	40	42	51	42	51	51
Naloop (mm)	102	98,9	94,3	98,9	94,3	94,3
Wielbasis (mm)	1072	1104	1119	1128	1139	1160
Liggende achtervork lengte (mm)	440	440	455	440	455	455
Bottom Bracket Drop (mm)	40	45	55	45	55	55
Stack (mm)	554	579	596	588	601	610
Reach (mm)	383	405	399	425	418	435
Stand Over Height (mm)	663	686	705	708	737	757
Stuur breedte (mm)	730	750	750	750	750	750
Stuurpen Lengte (mm)	40	40	40	50	50	50
Cranklengte (mm)	165	165	170	170	170	175
Wielmaat	27.5"	27.5"	29"	27.5"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.