# TEMPT 3




## SPEZIFIKATIONEN

| RAHMEN | |
|---|---|
| **GRÖSSEN** | 27.5": XS, S 29": S, M, L |
| **FARBE** | Morning Haze, Airglow |
| **RAHMEN** | ALUXX-grade aluminum, disc |
| **GABEL** | SR Suntour XCE, QR, steel steerer 27.5" XS: 80mm, S: 80mm 29" S: 100mm, M: 100mm, L: 100mm |
| **KOMPONENTEN** | |
| **LENKER** | Giant Connect Trail, 31.8mm 27.5" XS: 690mm, S: 690mm 29" S: 750mm, M: 750mm, L: 750mm |
| **GRIFFE** | Giant Sole-O |
| **VORBAU** | Giant Sport, 7-degree 27.5" XS: 40mm, S: 40mm 29" S: 40mm, M: 50mm, L: 50mm |
| **SATTELSTÜTZE** | Giant Sport, 30.9mm 27.5" XS:100x350mm, S: 100x350mm 29" S: 100x375mm, M:100x375mm, L: 100x375mm |
| **SATTEL** | Contact Ergo |
| **PEDALE** | MTB caged |
| **ANTRIEB** | |
| **SCHALTHEBEL** | Shimano, Acera 2x8, SL-M315-2L, SL-M315-8R |
| **UMWERFER** | Shimano, Acera, FD-M315-TS |
| **SCHALTWERK** | Shimano, Acera 2x8, RD M3020-8 |
| **BREMSEN** | Tektro, hydraulic, Tektro rotors [F]180mm, [R]160mm |
| **BREMSHEBEL** | Tektro |
| **KASSETTE** | Shimano, Acera, CS-HG31-8, 11-34 |
| **KETTE** | KMC 8.3 |
| **KURBEL** | Shimano Acera FC-M315-2, 22/36, 49mm chainline 27.5" XS: 170mm, S: 170mm 29" S: 170mm, M: 170mm, L: 170mm |
| **TRETLAGER** | cartridge |

| LAUFRÄDER | |
|---|---|
| **FELGEN** | Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width |
| **NABE** | [F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive |
| **SPEICHEN** | stainless, 14g |
| **REIFEN** | Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead |
| **LIMITS** | |
| **MAX TIRE CLEARANCE** | 2.4" |
| **MAX CHAINRING SIZE** | 32t |

## GEOMETRIEDATEN

| RAHMEN | XS (27.5") | S (27.5") | S (29") | M (29") | L (29") |
|---|---|---|---|---|---|
| Sitzrohrlänge (mm) | 330 | 365 | 380 | 410 | 440 |
| Seat Post Insertion Depth (mm) | 280 | 310 | 330 | 360 | 220 |
| Sitzrohrwinkel | 74.0° | 74.0° | 74.5° | 74.5° | 74.5° |
| Oberrohrlänge (mm) | 538 | 558 | 571 | 599 | 629 |
| Steuerrohr-Länge (mm) | 90 | 95 | 90 | 100 | 120 |
| Steuerrohr-Winkel | 67.0° | 67.0° | 67.5° | 67.5° | 67.5° |
| Gabelneigung (mm) | 44 | 44 | 44 | 44 | 44 |
| Trail (mm) | 105.2 | 105.2 | 108.9 | 108.9 | 108.9 |
| Radstand (mm) | 1080 | 1101 | 1129 | 1158 | 1190 |
| Kettenstreben-Länge (mm) | 440 | 440 | 455 | 455 | 455 |
| Tretlager-Höhe (mm) | 45 | 45 | 55 | 55 | 55 |
| Stack (mm) | 548 | 553 | 593 | 602 | 620 |
| Reach (mm) | 381 | 400 | 407 | 432 | 457 |
| Überstandshöhe (mm) | 680 | 689 | 689 | 708 | |
| Lenkerbreite (mm) | 690 | 690 | 690 | 690 | 760 |
| Vorbaulänge (mm) | 40 | 40 | 40 | 50 | 60 |
| Kurbellänge (mm) | 165 | 165 | 170 | 170 | 170 |

*Spezifikations-, Preis- und Farbänderungen vorbehalten.*