TEMPT 3



SPECS

FRAME	
SIZES	27.5": XS, S 29": S, M, L
COLOURS	Morning Haze, Airglow
FRAME	ALUXX-grade aluminum, disc
FORK	SR Suntour XCE, QR, steel steerer 27.5" XS: 80mm, S: 80mm 29" S: 100mm, M: 100mm, L: 100mm
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm 27.5" XS: 690mm, S: 690mm 29" S: 750mm, M: 750mm, L: 750mm
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree 27.5" XS: 40mm, S: 40mm 29" S: 40mm, M: 50mm, L: 50mm
SEATPOST	Giant Sport, 30.9mm 27.5" XS:100x350mm, S: 100x350mm 29" S: 100x375mm, M:100x375mm, L: 100x375mm
SADDLE	Contact Ergo
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	Shimano, Acera 2x8, SL-M315-2L, SL-M315-8R
FRONT DERAILLEUR	Shimano, Acera, FD-M315-TS
REAR DERAILLEUR	Shimano, Acera 2x8, RD M3020-8
BRAKES	Tektro, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRAKE LEVERS	Tektro
CASSETTE	Shimano, Acera, CS-HG31-8, 11-34
CHAIN	KMC 8.3
CRANKSET	Shimano Acera FC-M315-2, 22/36, 49mm chainline 27.5" XS: 170mm, S: 170mm 29" S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	cartridge

WHEELS	
RIMS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
HUBS	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
SPOKES	stainless, 14g
TYRES	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	32t

Price: €669.00

GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Seat Tube Length (mm)	330	365	380	410	440
Seat Post Insertion Depth (mm)	280	310	330	360	220
Seat Tube Angle	74.0°	74.0°	74.5°	74.5°	74.5°
Top Tube Length (mm)	538	558	571	599	629
Head Tube Length (mm)	90	95	90	100	120
Head Tube Angle	67.0°	67.0°	67.5°	67.5°	67.5°
Fork Rake (mm)	44	44	44	44	44
Trail (mm)	105.2	105.2	108.9	108.9	108.9
Wheelbase (mm)	1080	1101	1129	1158	1190
Chain Stay Length (mm)	440	440	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55
Stack (mm)	548	553	593	602	620
Reach (mm)	381	400	407	432	457
Stand Over Height (mm)	680	689	689	708	
Handlebar Width (mm)	690	690	690	690	760
Stem Length (mm)	40	40	40	50	60
Crank Length (mm)	165	165	170	170	170

All specifications listed are subject to change without notice.