



SPECS

FRAME	
SIZES	27.5": XS,S,M 29": S,M,L
COLORS	Metallic Black, Purple Ash
FRAME	ALUXX-Grade Aluminum, disc
FORK	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 100mm travel (27.5) / 100mm travel (29)
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm XS: 670mm (27.5) S: 670mm (27.5) / 670mm (29) M: 750mm (27.5) / 750mm travel (29) L: 750mm (29)
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree XS: 40mm (27.5) S: 40mm (27.5) / 40mm (29) M: 50mm (27.5) / 50mm travel (29) L: 50mm (29)
SEATPOST	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (29)
SADDLE	Liv Sport
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	microSHIFT, 2x8
FRONT DERAILLEUR	microSHIFT FD-M282
REAR DERAILLEUR	Shimano Altus M310
BRAKES	Tektro HDC TKD 149, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRAKE LEVERS	Tektro TKD 149
CASSETTE	Shimano Deore HG200, 12x32
CHAIN	KMC 8.3
CRANKSET	Shimano FC-M315, 22/36 XS: 170mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 170mm travel (29) L: 175mm (29)
BOTTOM BRACKET	cartridge

WHEELS	
RIMS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
HUBS	alloy, sealed bearing
SPOKES	stainless, 14g
TIRES	Kenda Booster 27.5" or 29x2.2", wire bead
EXTRAS	2.4" max tire size

GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Seat Tube Length (mm)	325	365	370	405	420	450
Seat Tube Angle	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	542	571	570	594	590	610
Head Tube Length (mm)	95	100	90	110	95	105
Head Tube Angle	68,0°	68,0°	68,5°	68,0°	68,5°	68,5°
Fork Rake (mm)	40	42	51	42	51	51
Trail (mm)	102	98,9	94,3	98,9	94,3	94,3
Wheelbase (mm)	1072	1104	1119	1128	1139	1160
Chain Stay Length (mm)	440	440	455	440	455	455
Bottom Bracket Drop (mm)	40	45	55	45	55	55
Stack (mm)	554	579	596	588	601	610
Reach (mm)	383	405	399	425	418	435
Stand Over Height (mm)	663	686	705	708	737	757
Handlebar Width (mm)	730	750	750	750	750	750
Stem Length (mm)	40	40	40	50	50	50
Crank Length (mm)	165	165	170	170	170	175
Wheel Size	27.5"	27.5"	29"	27.5"	29"	29"

All specifications listed are subject to change without notice.