TEMPT 3



SPECIFICATIES

FRAME	
MATEN	27.5": XS, S 29": S, M, L
KLEUREN	Morning Haze, Airglow
FRAME	ALUXX-grade aluminum, disc
VOORVORK	SR Suntour XCE, QR, steel steerer 27.5" XS: 80mm, S: 80mm 29" S: 100mm, M: 100mm, L: 100mm
ONDERDELEN	
STUUR	Giant Connect Trail, 31.8mm 27.5" XS: 690mm, S: 690mm 29" S: 750mm, M: 750mm, L: 750mm
HANDVATTEN	Giant Sole-O
STUURPEN	Giant Sport, 7-degree 27.5" XS: 40mm, S: 40mm 29" S: 40mm, M: 50mm, L: 50mm
ZADELPEN	Giant Sport, 30.9mm 27.5" XS:100x350mm, S: 100x350mm 29" S: 100x375mm, M:100x375mm, L: 100x375mm
ZADEL	Contact Ergo
PEDALEN	MTB caged
AFMONTAGE	
SHIFTERS	Shimano, Acera 2x8, SL-M315-2L, SL-M315-8R
VOORDERAILLEUR	Shimano, Acera, FD-M315-TS
ACHTERDERAILLEUR	Shimano, Acera 2x8, RD M3020-8
REMMEN	Tektro, hydraulic, Tektro rotors [F]180mm, [R]160mm
REMHENDELS	Tektro
CASSETTE	Shimano, Acera, CS-HG31-8, 11-34
AANDRIJVING	KMC 8.3
CRANKSET	Shimano Acera FC-M315-2, 22/36, 49mm chainline 27.5" XS: 170mm, S: 170mm 29" S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	cartridge

WIELSET	
VELGEN	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NAVEN	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
SPAKEN	stainless, 14g
BANDEN	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
LIMITS	
MAXIMALE BANDENVRIJHEID	2.4"
MAXIMALE KETTINGBLADMAAT	32t

Adviesprijs: € 649,00

GEOMETRIE

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Zitbuis Lengte (mm)	330	365	380	410	440
Seat Post Insertion Depth (mm)	280	310	330	360	220
Zitbuis Hoek	74,0°	74,0°	74,5°	74,5°	74,5°
Frame Lengte (horizontaal) (mm)	538	558	571	599	629
Balhoofdbuis Lengte (mm)	90	95	90	100	120
Balhoofdbuis Hoek	67,0°	67,0°	67,5°	67,5°	67,5°
Vork Sprong (mm)	44	44	44	44	44
Naloop (mm)	105,2	105,2	108,9	108,9	108,9
Wielbasis (mm)	1080	1101	1129	1158	1190
Liggende achtervork lengte (mm)	440	440	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55
Stack (mm)	548	553	593	602	620
Reach (mm)	381	400	407	432	457
Stand Over Height (mm)	680	689	689	708	
Stuur breedte (mm)	690	690	690	690	760
Stuurpen Lengte (mm)	40	40	40	50	60
Cranklengte (mm)	165	165	170	170	170

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.