TEMPT 3



SPECS

QUADRO	
TAMANHOS	27.5": XS, S 29": S, M, L
CORES	Morning Haze, Airglow
QUADRO	ALUXX-grade aluminum, disc
FORQUILHA	SR Suntour XCE, QR, steel steerer 27.5" XS: 80mm, S: 80mm 29" S: 100mm, M: 100mm, L: 100mm
COMPONENTES	
GUIADOR	Giant Connect Trail, 31.8mm 27.5" XS: 690mm, S: 690mm 29" S: 750mm, M: 750mm, L: 750mm
PUNHOS	Giant Sole-O
AVANÇO	Giant Sport, 7-degree 27.5" XS: 40mm, S: 40mm 29" S: 40mm, M: 50mm, L: 50mm
ESPIGÃO DE SELIM	Giant Sport, 30.9mm 27.5" XS:100x350mm, S: 100x350mm 29" S: 100x375mm, M:100x375mm, L: 100x375mm
SELIM	Contact Ergo
PEDAIS	MTB caged
TRANSMISSÃO	
MANETES	Shimano, Acera 2x8, SL-M315-2L, SL-M315-8R
DESVIADOR DIANTEIRO	Shimano, Acera, FD-M315-TS
DESVIADOR TRASEIRO	Shimano, Acera 2x8, RD M3020-8
TRAVÕES	Tektro, hydraulic, Tektro rotors [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Tektro
CASSETE	Shimano, Acera, CS-HG31-8, 11-34
CORRENTE	KMC 8.3
CONJUNTO PEDALEIRO	Shimano Acera FC-M315-2, 22/36, 49mm chainline 27.5" XS: 170mm, S: 170mm 29" S: 170mm, M: 170mm, L: 170mm
MOVIMENTO CENTRAL	cartridge

RODAS	
AROS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
CUBOS	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
RAIOS	stainless, 14g
PNEUS	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
LIMITES	
FOLGA MÁXIMA DO PNEU	2.4"
TAMANHO MÁXIMO DA COROA	32t

Preço: 649,00 €

GEOMETRIA

QUADRO	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Comprimento do tubo do assento (mm)	330	365	380	410	440
Seat Post Insertion Depth (mm)	280	310	330	360	220
Ângulo do tubo do assento	74,0°	74,0°	74,5°	74,5°	74,5°
Comprimento do tubo superior (mm)	538	558	571	599	629
Comprimento do tubo principal (mm)	90	95	90	100	120
Ângulo do tubo principal	67,0°	67,0°	67,5°	67,5°	67,5°
Garfo ancinho (mm)	44	44	44	44	44
Trilha (mm)	105,2	105,2	108,9	108,9	108,9
distância entre eixos (mm)	1080	1101	1129	1158	1190
Comprimento Chain Stay (mm)	440	440	455	455	455
Suporte inferior (mm)	45	45	55	55	55
Pilha (mm)	548	553	593	602	620
Alcançar (mm)	381	400	407	432	457
Altura do standover (mm)	680	689	689	708	
Largura do guidão (mm)	690	690	690	690	760
Comprimento da haste (mm)	40	40	40	50	60
Comprimento da Manivela (mm)	165	165	170	170	170

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.