



SPECIFIKACIJE

OKVIR	
VELIKOSTI	27.5": XS,S,M 29": S,M,L
BARVE	Metallic Black, Purple Ash
OKVIR	ALUXX-Grade Aluminum, disc
VILICE	SR Suntour XCE, QR, steel steerer XS: 80mm travel (27.5) S: 100mm travel (27.5) / 100mm travel (29)
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Connect Trail, 31.8mm XS: 670mm (27.5) S: 670mm (27.5) / 670mm (29) M: 750mm (27.5) / 750mm travel (29) L: 750mm (29)
GRIPS	Giant Sole-O
OPORA KRMILA	Giant Sport, 7-degree XS: 40mm (27.5) S: 40mm (27.5) / 40mm (29) M: 50mm (27.5) / 50mm travel (29) L: 50mm (29)
OPORA SEDEŽA	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (29)
SEDEŽ	Liv Sport
PEDALA	MTB caged
POGON	
PRESTAVNE ROČICE	microSHIFT, 2x8
PREDNJI MENJALNIK	microSHIFT FD-M282
ZADNJI MENJALNIK	Shimano Altus M310
ZAVORE	Tektro HDC TKD 149, hydraulic, Tektro rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Tektro TKD 149
VERIŽNIK	Shimano Deore HG200, 12x32
VERIGA	KMC 8.3
GONILKE Z VERIŽNIKI	Shimano FC-M315, 22/36 XS: 170mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 170mm travel (29) L: 175mm (29)
BOTTOM BRACKET	cartridge

OBROČNIKI

OBROČI	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
PESTA	alloy, sealed bearing
NAPERE	stainless, 14g
PLAŠČI	Kenda Booster 27.5" or 29x2.2", wire bead
DODATKI	2.4" max tire size

GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Dolžina sedežne cevi (mm)	325	365	370	405	420	450
Kot sedežne cevi	74,0°	74,0°	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	542	571	570	594	590	610
Višina glave okvirja (mm)	95	100	90	110	95	105
Krmlini kot	68,0°	68,0°	68,5°	68,0°	68,5°	68,5°
Zamik vpetja osi (mm)	40	42	51	42	51	51
Trail (mm)	102	98,9	94,3	98,9	94,3	94,3
Medosna razdalja (mm)	1072	1104	1119	1128	1139	1160
Dolžina cevi ob verigi (mm)	440	440	455	440	455	455
Bottom Bracket Drop (mm)	40	45	55	45	55	55
Oddaljenost zgornje cevi od gonilne osi (mm)	554	579	596	588	601	610
Doseg (mm)	383	405	399	425	418	435
Višina zgornje cevi (mm)	663	686	705	708	737	757
Širina krmila (mm)	730	750	750	750	750	750
Dolžina opore krmila (mm)	40	40	40	50	50	50
Dolžina gonilke (mm)	165	165	170	170	170	175
Velikost obročnikov	27.5"	27.5"	29"	27.5"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.